


ORDERING INFORMATION
Combo Flat Head Lok-Bolt

Catalog Number		Size	Drill Diameter	Minimum Embed.	Standard Box	Standard Carton	Wt./ 100
Carbon	Stainless						
5305	—	1/4" x 1 1/8"	1/4"	1"	100	1,000	2
5310	6170	1/4" x 2"	1/4"	1 1/8"	100	1,000	2 3/4
5315	6172	1/4" x 3"	1/4"	1 1/8"	100	1,000	3 3/4
5320	—	1/4" x 4"	1/4"	1 1/8"	100	500	4 1/2
5325	—	1/4" x 5 1/4"	1/4"	1 1/8"	100	500	6 1/2
5330	—	5/16" x 2 1/2"	5/16"	1 1/2"	100	1,000	4 1/2
5340	—	3/8" x 2 3/4"	3/8"	1 5/8"	50	500	7 1/2
5345	6174	3/8" x 4"	3/8"	1 5/8"	50	250	10 3/4
5350	6175	3/8" x 5"	3/8"	1 5/8"	50	250	14
5360	6176	3/8" x 6"	3/8"	1 5/8"	50	250	16

The published length is the minimum overall length of the anchor. Combo Flat Head Lok-Bolts do not have a compression ring.


Threshold Flat Head Lok-Bolt, Slotted

Catalog Number		Size	Drill Diameter	Minimum Embed.	Standard Box	Standard Carton	Wt./ 100
Carbon	Stainless						
5500	—	1/4" x 2"	1/4"	1 1/8"	100	1,000	2 1/2

The published length is the minimum overall length of the anchor. Threshold Flat Head Lok-Bolts do not have a compression ring.


Rod Hanger Lok-Bolt

Catalog Number		Size	Drill Diameter	Minimum Embed.	Standard Box	Standard Carton	Wt./ 100
Carbon	Stainless						
5810	—	1/4" x 1 1/2"	5/16"	1 1/2"	50	250	5 1/2
5815	—	3/8" x 1 7/8"	3/8"	1 5/8"	50	250	9
5825	—	1/2" x 2 1/4"	1/2"	2 1/4"	25	125	21

The published length is measured from below the washer to the end of the anchor. Rod Hanger Lok-Bolts do not have a compression ring.


Tie-Wire Lok-Bolt

Catalog Number		Size	Drill Diameter	Minimum Embed.	Standard Box	Standard Carton	Wt./ 100
Carbon	Stainless						
5700	—	5/16" x 1 1/2"	5/16"	1 1/2"	100	1,000	5 1/4

The published length is measured from below the head to the end of the anchor.


Lok-Bolt Extenders

Catalog Number		Size	Drill Diameter	Minimum Embed.	Standard Box	Standard Carton	Wt./ 100
Carbon	Stainless						
5684	5689	3/8" x 1"	3/8"	1 5/8"	50	500	3

Extenders are used for added length on all head styles.

