

LOW VOLTAGE

# Design Pro LED Well Lights

In-ground lighting that's above the norm.






POWERED BY  
DESIGN PRO LED  
TECHNOLOGY

This installation illuminated with  
Design Pro LED Well Lights






Name	<b>LED WELL LIGHT</b> LED technology in a versatile design with reversible support sleeve to accommodate uplighting when flush mounting or angled lighting are desired in a semi-recessed application. Fully adjustable and available in a wide variety of outputs and beam spreads.		
Ordering Guide	<b>4.5W Version</b> 15767 BKT - 10° spot 15768 BKT - 35° flood 15769 BKT - 60° wide flood	<b>8.5W Version</b> 15728 BKT - 10° spot 15747 BKT - 35° flood 15748 BKT - 60° wide flood	<b>12.4W Version</b> 15729 BKT - 10° spot 15757 BKT - 35° flood 15758 BKT - 60° wide flood
Housing	Cast aluminum fixture body with a heavy duty polypropylene sleeve and stainless steel gimble ring.		
Finish	Textured Black		
Light Source	Integrated LEDs and Driver, 2950K (-150/+175), High CRI		
Power Usage at 12V AC Input VA & Watts	15767, 15768, 15769 7.5VA, 4.5W	15728, 15747, 15748 12.2VA, 8.5W	15729, 15757, 15758 16.7VA, 12.4W
Operating Voltage Range	9V - 15V AC/DC		
Wiring	35" of useable #18-2, SPT-1W leads. Cable connector supplied.		
Optional Accessories	<b>Snap on Cowl:</b> 15701BKTP - Short 4.5W/8.5W, 15702BKTP - Short 12.4W, 15703BKTP - Long 4.5W/8.5W, 15704BKTP - Long 12.4W <b>Rockguards/ Glare Shield:</b> 15787BK - Fits all versions <b>Custom Lenses:</b> Amber - 4.5W/8.5W - 15875AMB, Amber - 12.4W - 15876AMB, Green - 4.5W/8.5W - 15885GRN, Green - 12.4W - 15886GRN, Frosted - 4.5W/8.5W - 15895FRO, Frosted - 12.4W - 15896FRO		
Notes	See photometrics on page 139. Kichler LED Comparison: 4.5W is approximately comparable to a 20W MR16, a 8.5W to a 35W MR16, and a 12.4W to a 50W MR16 Not for use with electronic transformers.		



	<b>15787 BK</b>	Name	<b>LED WELL LIGHT COVER</b>
		Housing	Rock guard accessory for Design Pro LED Well Light Series
		Finish	High Strength Polycarbonate
		For use with the following fixtures	Black Polycarbonate 15767BKT, 15768BKT, 15769BKT, 15728BKT, 15747BKT, 15748BKT, 15729BKT, 15757BKT, 15758BKT



15787 BK snaps easily into place on flat side of fixture's sleeve.