

16451-W

Decora Plus Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 20 Amp, 250 Volt, Back or Side Wire, NEMA 6-20R, 2-Pole, 3-Wire, Self-Grounding - White



UPC Code : 078477474266

Country Of Origin : Please Contact Customer Service.

RoHS Compliant : Yes



Available Colors :



Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage : Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40°C to 60°C

Material Specifications

Body Material : Thermoplastic Nylon

Clamp Nuts : Zinc-Plated Steel

Face Material : Thermoplastic Nylon

Ground Clips : Brass-Plated

Grounding Screw : Brass 8-32

Line Contacts : Brass Triple-Wipe .031 Thick

Terminal Screws : Brass 10-32

Yoke : Zinc-Plated Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 10-14 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, White-Neutral

Termination : Back or Side Wire

Product Features

Amperage : 20 A

Body Material : Thermoplastic Nylon

Brand : Decora Plus

Color : White

Device Type : Single Receptacle Outlet

Face Material : Thermoplastic Nylon

Feature 4 : Smooth Face

Grade : Commercial Specification Grade

Grounding : Self-Grounding

NEMA : 6-20R

Pole : 2

Standards and Certifications : UL

Strap Material : Steel

Termination : Back or Side Wire

Voltage : 250 VAC

Warranty : 10-Year Limited

Wire : 3

Standards and Certifications


ANSI : C-73

NEMA : WD-6

NOM : 057

UL498 : File E13399

Wiring Diagram



6-15R

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

