



This High Tension Hack Saw Frame features a **NEW Cushin' Grip** handle and end pieces made of die cast aluminum. It is light weight yet extremely rigid and high tensioned; which provides cleaner, surer cuts. The blade can be set at a 55° angle for special flush cutting jobs (see figure A). The blade can also be inserted into the front end of the hack saw frame, and used as a versatile compass saw (see figure B). This frame fits most standard tool boxes.

- ◆ RED Cast Aluminum
- ◆ Light Weight
- ◆ Extremely Rigid
- ◆ Versatile
- ◆ 25,000 lbs Per Square Inch
- ◆ Includes 1 12" x 24T Bi-Metal Blade


High Tension Hack Saw Frame

Part #	Description	List
278HX0002	High Tension Hack Saw Frame	\$24.97



Hack Saw Blades - Bi-Metal

Part #	OAL	Teeth Per Inch	Wide	Thick	QTY.	List
278BM0018	12"	18T	1/2"	.025	10	\$1.99
278BM0024	12"	24T	1/2"	.025	10	\$1.99
278BM0032	12"	32T	1/2"	.025	10	\$1.99



Made In



- ◆ Made In USA
- ◆ Bi-Metal
- ◆ Premium Quality
- ◆ White Finish

Band Saw Blades - Bi-Metal

Part #	OAL	Teeth Per Inch	Wide	Thick	QTY.	List
279SB0010	44-7/8"	10T	1/2"	.020	3	\$10.92
279SB0014	44-7/8"	14T	1/2"	.020	3	\$10.92
279SB0018	44-7/8"	18T	1/2"	.020	3	\$10.92
279SB0024	44-7/8"	24T	1/2"	.020	3	\$10.92
279VP1014	44-7/8"	10/14	1/2"	.020	3	\$10.92
279VP1418	44-7/8"	14/18	1/2"	.020	3	\$10.92



Made In



- ◆ Made In USA
- ◆ Bi-Metal
- ◆ Premium Quality
- ◆ Standard or Variable Pitch
- ◆ Use In All Hand Held Band Saws