

Malleable Iron Threaded Conduit Bodies

For Threaded Rigid Conduit and IMC

Application:

To provide access to conductors for pulling, splicing, and maintenance. Threaded for rigid conduit and IMC.

Features:

- Tapered threaded hubs (NPT)
- Flat back design for easy mounting close to walls
- Suitable for use in concrete

Standard Materials:

Malleable Iron


Standard Finish:

Zinc Plated and Aluminum Enameled

 **UL Listed:**
E121488




Type LL1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MAXIMUM WIRE SIZE	VOL. CU. IN.	UNIT PACK	STANDARD PACK	WEIGHT (LBS.) PER 100 PCS.	NAED MFG #78-5994 UPC/DCI #
LL TYPE										
LL1	1/2"	4.688	2.063	1.375	N/A	4.50	10	50	76	41011
LL2	3/4"	5.375	2.250	1.688	3 #6 AWG	7.50	10	50	95	41021
LL3	1"	6.188	2.625	1.875	3 #4 AWG	12.50	5	25	138	41031
LL4	1-1/4"	8.125	2.750	2.750	3 #2 AWG	32.30	-	10	309	41041
LL5	1-1/2"	8.125	3.500	2.813	3 #1/0 AWG	35.30	-	10	332	41051
LL6	2"	10.500	4.125	3.313	3 #4/0 AWG	73.00	-	5	497	41061
LL7	2-1/2"	13.625	4.688	3.875	3 #300 MCM	138.00	-	1	1105	41071
LL8	3"	13.875	5.875	4.750	3 #350 MCM	170.00	-	1	1437	41081
LL9	3-1/2"	16.250	6.125	5.625	3 #350 MCM	300.00	-	1	2321	41091
LL10	4"	16.250	6.938	5.625	3 #350 MCM	328.00	-	1	2431	41101



Type LR1



CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	MAXIMUM WIRE SIZE	VOL. CU. IN.	UNIT PACK	STANDARD PACK	WEIGHT (LBS.) PER 100 PCS.	NAED MFG #78-5994 UPC/DCI #
LR TYPE										
LR1	1/2"	4.688	2.063	1.375	N/A	4.50	10	50	71	42011
LR2	3/4"	5.375	2.250	1.688	3 #6 AWG	7.50	10	50	100	42021
LR3	1"	6.188	2.625	1.875	3 #4 AWG	12.50	5	25	157	42031
LR4	1-1/4"	8.125	2.750	2.750	3 #2 AWG	32.30	-	10	332	42041
LR5	1-1/2"	8.125	2.813	2.813	3 #1/0 AWG	35.30	-	10	345	42051
LR6	2"	10.500	4.438	3.313	3 #4/0 AWG	73.00	-	5	626	42061
LR7	2-1/2"	13.625	5.375	3.875	3 #300 MCM	138.00	-	1	1105	42071
LR8	3"	13.875	5.875	4.750	3 #350 MCM	170.00	-	1	1437	42081
LR9	3-1/2"	16.250	6.875	5.625	3 #350 MCM	300.00	-	1	2321	42091
LR10	4"	16.625	7.188	5.625	3 #350 MCM	328.00	-	1	2500	42101