


Rigid Conduit Bodies Threaded T Type



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1

Features

- Threaded T type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast

Standard Finish

- Powder coat

Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
T1	21730	1/2"	1	6 AWG	10	100	32	4.72	1.37	2.03
T2	21740	3/4"	2	6 AWG	10	50	26	5.57	1.625	2.335
T3	21750	1"	3	6 AWG	5	25	18	6.46	1.90	2.705
T4	21760	1-1/4"	3	2 AWG	2	10	17	8.528	2.77	3.63
T5	21770	1-1/2"	3	2 AWG	2	10	19	8.528	2.77	3.63
T6	21780	2"	3	2/0 AWG	---	5	7	10.831	3.335	3.98
T7	21790	2-1/2"	3	4/0 AWG	---	1	7	13.50	4.06	5.825
T8	21800	3"	3	250 MCM	---	1	7	13	4.685	5.825
T9	21810	3-1/2"	3	350 MCM	---	1	9	15.937	5.45	7.06
T10	21820	4"	4	350 MCM	---	1	9	15.937	5.45	7.06

Rigid Conduit Bodies with Cover and Gasket Threaded LB Type



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1

Features

- Threaded LB type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat

Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	A	B	C
			Max. Number	Max. Size						
LB1CG	20841	1/2"	1	6 AWG	10	100	34	4.295	2.15	1.33
LB2CG	20851	3/4"	2	6 AWG	10	50	23	5.09	2.43	1.54
LB3CG	20861	1"	3	6 AWG	5	25	19	5.915	2.765	1.74
LB4CG	20871	1-1/4"	3	2 AWG	2	10	14	7.894	3.665	2.49
LB5CG	20881	1-1/2"	3	2 AWG	2	10	15	7.894	3.665	2.49
LB6CG	20891	2"	3	2/0 AWG	1	5	14	10.134	4.275	3.10
LB7CG	20901	2-1/2"	3	2/0 AWG	---	1	7	12.50	5.437	4.45
LB8CG	20911	3"	3	4/0 AWG	---	1	7	12.50	5.675	4.45
LB9CG	20921	3-1/2"	3	400 MCM	---	1	10	15.50	6.922	5.50
LB10CG	20931	4"	3	400 MCM	---	1	10	15.50	6.922	5.50