


EMT Elbows

30° - Galvanized Steel



UL 797 and ANSI C80.3
Fed. Spec. WW-C-563



Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit

Standard Material


- Galvanized steel

Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End
8430	83903	1-1/4"	---	30	19	7.25	2.781
8530	83893	1-1/2"	---	15	25	8.25	2.781
8630	83905	2"	---	10	20	9.50	2.781
8730	83906	2-1/2"	1	50	161	10.50	3
8830	83907	3"	1	35	153	13	3.125
8930	83908	3-1/2"	1	35	244	15	3.281
89A30	83909	4"	1	35	309	16	3.375

22.5° - Galvanized Steel



UL 797 and ANSI C80.3
Fed. Spec. WW-C-563



Features

- Low conductivity, high corrosion resistance
- Smooth defect free interior and exterior

Applications

- For a secure connection to EMT conduit; bend enables directional changes in conduit

Standard Material

- Galvanized steel

Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	(A) Min. UL Radius	(B) Straight Leg Each End
8422	83889	1-1/4"	---	30	17	7.25	2.781
8522	83890	1-1/2"	---	15	24	8.25	2.781
8622	83891	2"	---	10	18	9.50	2.781
8722	83892	2-1/2"	1	50	150	10.50	3
8822	83893	3"	1	35	175	13	3.125
8922	83994	3-1/2"	1	35	210	15	3.281
89A22	83995	4"	1	35	280	16	3.375