Power Supply Cords

2-Pole, 3-Wire Grounding 3-Pole, 3-Wire Non-Grounding





FEATURES

- Insulation stripped 0.75" (19.05mm).
 - For replacement use.
- Matching color molded plug.





Disposal Cord - 2-Pole, 3-Wire Grounding

Plug Rating

radiig								
Α	V/AC	NEMA	Cord Type	Cord Rating	Length	Catalog No.		
15	125	5-15	16/3 SJT	13A 125V	3' (0.91m) 6' (1.83m)	236 236-6		
					0 (1.65111)	230-0		

3-Wire Dryer/Range Cord with Angle Plug

FEATURES

- Brass terminal lugs provide superior conductivity and low heat rise characteristics.
- Strain relief clamp mounts to appliance and protects cord from damage caused by pulling or stretching.
- Angle plug allows cord to remain flush to wall in tight fitting spaces.
- Matching color molded plug.

Dryer Cord with Angle Plug - 3-Pole, 3-Wire

Plug Rating

Α	V/AC	NEMA	Cord Type	Cord Rating	Color	Length	Catalog No.
30	125/250	10-30	10/3 SRDT	30A 125/250V	Gray	4' (1.22m)	46-4
						5' (1.52m)	46-5
						6' (1.83m)	46-6



Range Cord with Angle Plug - 3-Pole, 3-Wire

Plug

Kati	kating						
Α	V/AC	NEMA	Cord Type	Cord Rating	Color	Length	Catalog No.
40	125/250	10-50	8/2/10 SRDT	40A 125/250V	Gray	4' (1.22m)	48-4
						6' (1.83m)	48-6
50	125/250	10-50	6/2/8 SRDT	50A 125/250V	Gray	4' (1.22m)	47-4
						5' (1.52m)	47-5
						6' (1.83m)	47-6











10-30P

10-50P

