PL H 6W BYP GU24 TITANIUM LED SERIES









- Built-in universal voltage driver Bypass installation
- Compatible with GU24 bases
- Exceptional efficacy 93 LPW
- Lasts 4 times longer than CFL
- Ompact form factor fits most fixtures
- Available in 3000K, 3500K & 4000K


























PL PRODUCT FEATURES

BYPass Installation

This PL H lamp requires bypassing the ballast during installation and runs directly off line voltage to eliminate compatibility problems, incidental power loss, lifetime issues, and maintenance costs associated with ballasts.




Adjustable Base





This PL H lamp features a base that can be rotated 310° to fit any socket configuration. After installation simply rotate the lamp to achieve maximum light output.

PL H 6W BYP GU24 TITANIUM LED SERIES









1.34"(34mm)

- 5.02"(128mm)

Base: GU24

Voltage: 120-277V

Dimmable: No PF: 0.9

Lifetime: 50,000 hrs
Weight: 0.15lb / 68g

SPECIFICATIONS*

Model	Product	Power (W)	сст	CRI (typ.)	Lumens	LPW	Beam Angle
6PLH/830/BYP/GU24	57928	6	Warm White 3000K	80	550	92	110°
6PLH/835/BYP/GU24	57929	6	Neutral White 3500K	80	550	92	110°
6PLH/840/BYP/GU24	57930	6	Cool White 4000K	80	560	93	110°

- * Specification data is preliminary and may be subject to change
- ** Suitable for damp locations. Not for use where directly exposed to weather or water
- *** Not intended for use in enclosed fixture:
- **** Full installation guide and more details available on website