


Medium Duty Toggle Switches



- Great for Light Household Appliances & Equipment
- 70062 is Perfect for Battery-Powered Equipment including Lawn Mowers and Trimmers
- 1/2" Mounting Hole
- Dielectric Strength: 1500V
- Insulation Resistance: 500V




CAT. NO.	TYPE	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	LOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
70050	TOGGLE WITH ON/OFF FACEPLATE WIRE LEAD	SPST	ON-OFF	6" WIRE LEADS	N/A	8A 125VAC 4A 250VAC 1/3HP 125V	.98 X .62 X .62	1	10
70060	TOGGLE WITH ON/OFF FACEPLATE	SPST	ON-OFF	SCREWS	2	6A 125VAC 3A 240VAC	.69 X .57 X .40	1	10
70062	TOGGLE SWITCH	SPST	ON-OFF	QUICK CONNECT SPADE	1	21A 12VDC	.69 X .55 X .45	1	10
70061	SHORT BALL BAT TOGGLE SWITCH WITH ON/OFF PLATE	SPST	ON-OFF	6" WIRE LEADS	N/A	6A 125VAC 3A 250VAC	.69 X .55 X .34	1	10



Non-Metallic Toggle Switches



- Great for Automotive, Recreational Equipment, and Marine Applications
- Double Insulated with Internal O-Ring for Moisture and Dust Resistance
- 1/2" Mounting Hole
- Dielectric Strength: 1500V
- Insulation Resistance: 500V
- () = Momentary



CAT. NO.	POLES	FUNCTION	TERMINAL TYPE	NO. OF TERMINALS	LOAD RATING	DIMENSIONS L" X W" X H"	BAG QTY	MASTER BAG
70120	SPST	ON-OFF	SCREW	2	20A 125VAC 10A 277VAC	1.37 X .76 X .94	1	10
70125	SPDT	MOMENTARY (ON)-OFF-(ON)	QUICK CONNECT SPADE	3	20A 125VAC 10A 277VAC	1.37 X .76 X .94	1	10
70127	DPDT	MOMENTARY (ON)-OFF-(ON)	QUICK CONNECT SPADE	6	20A 125VAC 10A 277VAC	1.37 X .76 X .94	1	10

