



General Characteristics

Fixture Life Hours	50000 Hours
Material	Steel
Lens Material	Acrylic
Lens Finish	White
Finish	Brushed Nickel
Life (based on 3hr/day)	45.7000000000
Safety Rating	ETL - Damp Location
Ingress Protection	IP40 (1 mm solids, Not protected from liquids)
Energy Star	True

Electrical Characteristics

Watts	20
Volts	120
Equivalent Watts	100
LED Chip Manufacturer	2835 Bridgelux
Power Factor	0.98
Operating Temperature	-20+55°C

Light Characteristics

Brightness	1400 Lumens
Color Accuracy (CRI)	80
Light Appearance	Warm White
Color Temperature	3000K
Beam Angle	150°

Product Dimensions

Size	18"
Item Dimensions (in)	(W) 2.5 (H) 4.5 (D) 18

Product Data

Item Number	81198-SU
Case Quantity	6.000000
Barcode on SKU	653703811987
Brand	Sunlite
Description	LFX/BAR/20W/30K/18"/BN/ACRYL
Energy Star File Number	2363419

Additional Features

ENERGY STAR CERTIFIED	True
UL RATING	ETL - Damp Location

Fixture Characteristics

Style	Traditional
Shape	Linear
Number of Lights	1 - Light



Item: 81198-SU
LFX/BAR/20W/30K/18"/BN/ACRYL

Mounting
Use Location

Wall
Indoor