




# POWER CONNECTORS

## Long Barrel Aluminum 2 Hole Compression Lugs



- Lugs accept both aluminum and copper conductors
- Connector bores are coated with oxide inhibitor & capped
- Made of high-conductivity seamless aluminum
- Uniform bright electro-tin plating resists corrosion, reduces contact resistance and gives you maximum conductivity
- Color Coded for easy identification
- Marked with die index
- Crimp marks indicate proper crimp locations
- UL486B Listed AL9CU
- Listed for 35 KV when properly installed



Dimension Measurements = Inches & (Millimeters)



Cat No.	Wire Range	Stud Size	Color Code	Box Qty	Inside Diameter	Outside Diameter	A	A1	B	C	D	E	F	G	Each
93110	1/0 Str.	3/8	Tan	10	.39(9.91)	.63(16.00)	3.50(88.9)	1.2(30.5)	.85(21.5)	.24(6.1)	.41(10.4)	.38(9.6)	1.87(47.5)	1.00(25.4)	
93111	1/0 Str	1/2	Tan	20	.39(9.91)	.63(16.00)	4.75(120.6)	1.2(30.5)	.85(21.5)	.24(6.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93112	2/0 Str.	1/2	Olive	20	.44(11.18)	.69(17.53)	4.80(121.9)	1.3(33.0)	.94(23.8)	.24(6.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93114	3/0 Str.	1/2	Ruby	20	.48(12.19)	.76(19.30)	5.00(127.0)	1.4(35.6)	1.03(26.1)	.28(7.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93116	4/0 Str.	1/2	White	12	.55(13.97)	.84(21.34)	5.25(133.3)	1.4(35.6)	1.15(29.2)	.29(7.3)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93118	250 MCM	1/2	Red	12	.59(14.99)	.92(23.37)	5.31(134.8)	1.5(38.1)	1.26(32.0)	.32(8.1)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93120	300 MCM	1/2	Blue	9	.65(16.51)	1.01(25.65)	5.50(139.7)	1.6(40.6)	1.37(34.8)	.35(8.8)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93122	350 MCM	1/2	Brown	6	.72(18.29)	1.12(28.45)	5.87(149.1)	1.9(48.3)	1.52(38.6)	.39(9.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93124	400 MCM	1/2	Green	6	.76(19.30)	1.19(30.23)	6.43(163.3)	2.3(58.4)	1.61(40.8)	.42(10.6)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93126	500 MCM	1/2	Pink	6	.84(21.34)	1.32(33.53)	6.50(165.1)	2.5(63.5)	1.79(45.4)	.47(11.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93128	600 MCM	1/2	Black	4	.92(23.37)	1.44(36.58)	6.75(171.4)	2.6(66.0)	1.96(49.7)	.51(12.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	
93130	750 MCM	1/2	Yellow	4	1.03(26.16)	1.60(40.64)	7.37(187.2)	3.2(81.3)	2.19(55.6)	.55(13.9)	.51(12.9)	.63(16.0)	3.12(79.2)	1.75(44.4)	