

Project:

Type:

Prepared By:

Date:



UPC: 019813833903



### Features and Benefits

Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Environmentally friendly, no mercury used

UL Listed, ENERGY STAR Compliant

Non-Dimmable

Universal Voltage 120 through 277V

50,000 hour Lifespan

5 Year No Compromise Warranty

## Technical Specifications

### Performance

#### Product Type:

A-Line

#### Input Wattage:

23.5W

#### Typical Lumen Output:

3010

#### Efficacy:

125 lm/W

#### Color Temperature:

3000K Warm White

#### CRI:

80

### L70 Lifespan:

40,000 Hours

### Dimmable:

No

### Construction

#### Bulb Shape:

A23 E26

#### Base Type:

E26

#### Beam Angle:

230°

### Other

#### Equivalency:

200WW Incandescent

### Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

### Electrical

#### Power Factor:

>0.9

#### Operating Temperature:

-20°C - 45°C

#### Input Voltage:

120-277V AC

#### Operating Frequency:

60 Hz

## Technical Specifications (continued)

### Technical Specifications

#### For Use Outdoors in Open Fixtures:

No

### Electrical Characteristics

#### Input Current @ 120V:

249mA

#### Input Current @ 277V:

108mA

#### THDi:

≤25%

### Compliance

#### UL Listed:

Yes

#### UL Classified:

Yes

#### CEC Status:

Not lawful for sale in California

### ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

#### Energy Star ID:

2341112

## Case and Pallet Dimensions

|        | QTY | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|-----|-------------|------------|-------------|
| CASE   | 12  | 10.8        | 7.5        | 14.4        |
| PALLET | 864 | 44.9        | 47.3       | 44.5        |

## Dimension

