

Spacers

Carlton Snap-N-Stac combo spacers

Carlton Snap-N-Stac combo spacers

Cat. No.	Description	Size (in.)	Separation (in.)	Std. Ctn.	Std. Wt. (lbs.)
SP2W20-1	1-way spacers	2	2	56	15.0
SP2W30-1		2	3	40	13.0
SP4W15-1		4	1½	26	9.6
SP4W20-1		4	2	20	10.0
SP4W30-1		4	3	20	9.4
SP2W20-2*	2-way spacers	2	2	56	28.5
SP2W30-2*		2	3	40	23.8
SP3W20-2		3	2	40	24.0
SP3W30-2		3	3	24	17.9
SP4W15-2*		4	1½	26	18.3
SP4W20-2*		4	2	24	18.8
SP4W30-2*		4	3	20	17.6
SP5W20-2		5	2	20	17.2
SP5W30-2		5	3	14	15.5
SP6W20-2		6	2	12	12.8
SP6W30-2	3-way spacers	6	3	12	14.1
SP2W20-3		2	2	36	28.5
SP2W30-3		2	3	18	17.8
SP4W15-3		4	1½	18	19.4
SP4W20-3		4	2	16	19.3
SP4W30-3		4	3	14	19.1

*Can be cut apart to make (2) one-way spacers.

How to interpret the part number:


Position 1	Position 2	Position 3	Position 4
Product type	Duct size	Duct-to-duct spacing horizontal and vertical	Horizontal duct positions
SP = Spacer	2W = 2" width	15 = 1½"	-1 = one-way
	3W = 3" width	20 = 2"	-2 = two-way
	4W = 4" width	30 = 3"	-3 = three-way
	5W = 5" width		
	6W = 6" width		

Accessories

Snap-Loc reducer

	Cat. No.	Size (in.)	Std. Ctn.
	S287F	1	100
	S287J	2	100

Beaded strap

	Cat. No.	Std. Ctn.
	S28612	100

15" in length

Technical information

Cat. No.	Duct size (in.)	Duct O.D.	Duct-to-Duct Spacing		Center-to-Center Spacing		Horizontal (in.)	Bottom of trench to bottom of duct	Bottom of Trench to center of bottom of duct	Overall length
			Horizontal duct positions	Vertical (in.)	Horizontal (in.)	Vertical (in.)				
SP2W20-1	2	2.375	1	2	2	2.19	2.19	3.13	4.25	4.38
SP2W30-1	2	2.375	1	3	3	2.69	2.69	4.13	5.25	5.38
SP4W15-1	4	4.500	1	1.5	1.5	3.00	3.00	3.38	5.56	6.00
SP4W20-1	4	4.500	1	2	2	3.25	3.25	3.88	6.06	6.50
SP4W30-1	4	4.500	1	3	3	3.75	3.75	4.88	7.06	7.50
SP2W20-2	2	2.375	2	2	2	4.38	4.38	3.13	4.25	8.75
SP2W30-2	2	2.375	2	3	3	5.38	5.38	4.13	5.25	10.75
SP3W20-2	3	3.500	2	2	2	5.50	5.50	3.63	5.38	11.00
SP3W30-2	3	3.500	2	3	3	6.50	6.50	4.63	6.38	13.00
SP4W15-2	4	4.500	2	1.5	1.5	6.00	6.00	3.38	5.56	12.00
SP4W20-2	4	4.500	2	2	2	6.50	6.50	3.88	6.06	13.00
SP4W30-2	4	4.500	2	3	3	7.50	7.50	4.88	7.06	15.00
SP5W20-2	5	5.500	2	2	2	7.56	7.56	4.38	7.25	15.12
SP5W30-2	5	5.500	2	3	3	8.56	8.56	5.38	8.25	17.14
SP6W20-2	6	6.625	2	2	2	8.62	8.62	4.13	7.38	17.25
SP6W30-2	6	6.625	2	3	3	9.62	9.62	5.13	8.38	19.25
SP2W20-3	2	2.375	3	2	2	4.38	4.38	3.13	4.25	13.13
SP2W30-3	2	2.375	3	3	3	5.38	5.38	4.13	5.25	16.13
SP4W15-3	4	4.500	3	1.5	1.5	6.00	6.00	3.38	5.56	18.00
SP4W20-3	4	4.500	3	2	2	6.50	6.50	3.88	6.06	19.50
SP4W30-3	4	4.500	3	3	3	7.50	7.50	4.88	7.06	22.50