## ASOA – OASIS™ WALL FAN HEATER







# **Pasis**

# MAKE YOUR BATHROOM AN OASIS OF PEACE AND TRANQUILITY

The quiet and discreet Oasis bathroom fan heater provides all the comfort you need. It features a highly accurate electronic thermostat and optimal heat output, so you can easily and rapidly control the comfort-level of your rooms. Also offered without a thermostat, it's the perfect little device to heat small rooms like vestibules or hallways. In addition, its refined look and high-performance polymer finish blend in with any decor.

- ULTRA-QUIET FAN HEATER
- HEAT "BOOST" MODE FAST TEMPERATURE INCREASE (1000 W TO 2000 W) †
- FEATURING HIGH-PERFORMANCE POLYMER AND SATIN-FINISH PAINTED STEEL
- OPTIONAL BUILT-IN ELECTRONIC THERMOSTAT

#### **COLOR**

• white

#### **FINISH**

· epoxy-polyester powdercoat

#### **MANUFACTURING**

- high performance polymer cabinet and front edges, 20-gauge satin-finish steel front
- centrifugal fan that ensures a quiet and efficient airflow
- thermal protections with manual reset
- top front air intake and bottom front air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (ASOA1501PW model)

#### **ELEMENT**

 high-quality nichrome element that generates instant heat

#### CONTROL

MODEL WITHOUT A THERMOSTAT:

• an electronic wall thermostat is recommended

MODEL WITH A BUILT-IN THERMOSTAT:

- · built-in electronic thermostat
- 1000 W to maintain temperature setpoint
- 2000 W when "boost" mode is activated (with a timer)
- drastic temperature drop detection (open window function)

#### **INSTALLATION**

- recessed or surface mounted surface adapter not required
- on the wall, a minimum of 6 in. from the floor
- front easy to install with only one mounting screw
- power switch selector 1000 W or 2000 W (model without a thermostat only)

#### WARRANTY

five years, \*three years on electronic components

 $\dagger$  9°F temperature rise within five minutes. (Tests performed with the 2000 W model in a 70 ft<sup>2</sup> room.)



**IDEAL FOR:** 

bathroom, entrance, vestibule, hallway, living space







TECHNICAL SPECIFICATIONS										
PRODUCT	WITH THE HEATING		ERMOSTAT HEAT "BOOST" MODE		WITHOUT THERMOSTAT		VOLTAGE	HEIGHT	LENGTH	WEIGHT
CODE	WATTS	BTU/H	WATTS	BTU/H	WATTS	BTU/H	VOLTS	IN.	IN.	LB
ASOA1501W	1000	3413	1500	5119			120	15 13/16	12	7.9
ASOA1501WCW					1500	5119	120	15 13/16	12	7.9
ASOA2002W	1000/750	3413/2560	2000/1500	6825/5119			240/208	15 13/16	12	7.9
ASOA2002WCW					2000/1500 or 1000/750*	6825/5119 or 3413/2560*	240/208	15 13/16	12	7.9
MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET)										
ASOA1501PW	1000	3413	1500	5119			120	15 13/16	12	7.9

<sup>\*</sup> Selected when installed with a power switch.

### **TECHNICAL DRAWINGS**

