

architectural fluorescent light bars



Most Sustainable Choice

Model	Lamp		Finish			Dimensions
13 1/8 Inches	Fluorescent T5	Lumens	BB	SN	WT	
BA-F108	1 x F8T5, 8w	340	•	•	•	13 1/8" L x 5" W x 1 1/4" H

Order lamp separately. Select from a range of color temperature choices



Model	Lamp		Finish			Dimensions
22 Inches	Fluorescent T5	Lumens	BB	SN	WT	
BA-F113	1 x F13T5, 13w	750	•	•	•	22" L x 5" W x 1 1/4" H

Order lamp separately. Select from a range of color temperature choices



Model	Lamp		Finish			Dimensions
25 3/8 Inches	Fluorescent T5	Lumens	BB	SN	WT	
BA-F208	2 x F8T5, 8w	680	•	•	•	25 3/8" L x 5" W x 1 1/4" H

Order lamps separately. Select from a range of color temperature choices



Model	Lamp		Finish			Dimensions
34 3/8 Inches	Fluorescent T5	Lumens	BB	SN	WT	
BA-F813	1 x F8T5 + 1 x F13T5, 21w	1020	•	•	•	34 3/8" L x 5" W x 1 1/4" H

Order lamp separately. Select from a range of color temperature choices



Model	Lamp		Finish			Dimensions
43 1/4 Inches	Fluorescent T5	Lumens	BB	SN	WT	
BA-F213	2 x F13T5, 26w	1500	•	•	•	43 1/4" L x 5" W x 1 1/4" H

Order lamp separately. Select from a range of color temperature choices



POWER CORD

Model	BA-PC6
Finish	WT White
Length	6'

Easy to connect grounded power cord requires no additional wiring for installation. Allows Light Bars to be powered in any application



"I" CONNECTOR

Model	BA-I
Finish	WT White

Interconnection system for seamless end to end transitions. An "I" Connector is included with each light bar



INTERCONNECT CABLE

Model	BA-IC12	BA-IC24	BA-IC36
Finish	WT	White	
Length	12"	24"	36"

Interconnect cable allows the linking of two light bars in any direction using a single power connection. Perfect for joining fixtures at a corner to maintain even light distribution

Finish Key BB-Bronze, SN-Satin Nickel, WT-White 