



Indoor fixtures for use below 25'. 16" units for 250w Metal Halide. 22" units for 400w Metal Halide. Die cast aluminum housing and wiring box. Clear acrylic Lexalite Reflexor prismatic refractor. Ballast and lamp supplied.

Color: N/A

Weight: 30.7 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

Type: ED37
 Watts: 400W
 Shape/Size: N/A
 Base: N/A
 ANSI: N/A
 Hours: 20,000
 Lamp Lumens: 41,000
 Efficacy: 91 LPW

Ballast Info

Type: CWA-HPF QT
 120V: 3.5/4.0A
 208V: 2.0/2.3A
 240V: 1.8/2.0A
 277V: 1.5/1.8A
 Input Watts: 449W
 Efficiency: 89%

Technical Specifications

Listings

UL Listing:

UL Listed for 65° C (149° F) ambient temperature. Damp locations.

UL Listing:

Suitable for damp locations. UL and cUL listed for 40°C (104°F) ambient temperature.

Construction

Housing:

Heavy die cast aluminum housing with powder coat finish.

Junction Box:

Heavy duty stamped steel junction box.

Housing:

Die cast aluminum housing with an open air ballast for cooler operation.

Plate:

Die-cast plate tapped 3/4" NPS accepts 3/4" pipe or 715NEW die cast hook.

Reflector:

Reflector with five distribution patterns for precise control.

Housing:

Die cast aluminum housing and wiring box with 1/2" NPS knockouts and easy leveling adjustment. Comes with 3' cord, hook/loop and safety chain.

Bracket:

Multi-position adjustable reflector bracket.

Electrical

Socket:

Mogul base open rated socket.

Ballast:

Quad Tap. All fixtures are wired for 277V at the factory.

Ballast:

Multi-Tap Ballast (120/208/240/277 Volts).

Ballast:

High power factor ballast with class H insulation.

Socket:

4Kv pulse rated mogul-base porcelain socket, spring loaded center contact.

Wiring Compartment:

Removable steel wiring compartment door for quick and easy mounting.

Start Up Time:

3 - 5 minutes.

Restrike Time:

10 - 20 minutes.

Pulse Start:

Pulse Start metal halide for increased lamp life, lumen maintenance, color uniformity and efficiency.

Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volts).

Socket:

4KV pulse rated mogul base socket.

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code .

Optical

Patterns:

Field adjustable light distribution patterns.

Lamp:

Mogul Base, ED18.

Reflector:

Seven distribution patterns for precise control with seven position adjustable bracket. Clear acrylic Lexalite Reflexor_ prismatic refractor for long-term resistance to yellowing.

Other

Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

Technical Specifications (continued)

Other

Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

Dimensions



Features

CSA Certified for Indoor Locations

Supplied with safety hook and 3 foot cord

Use indoors below 25'

Ballast and lamp included