



Upscale design, high-end performance, undeniable value. BOA is designed with proprietary optics that deliver maximum lumens and conceal the LED light sources behind the lens to create a pleasing dimensional illuminance with soft blended beam edges.

Color: White

Weight: 19.4 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type: Constant Current
 120V: 0.24A
 208V: 0.18A
 240V: 0.16A
 277V: 0.15A
 Input Watts: 27W
 Efficiency: N/A

LED Info

Watts: 30W
 Color Temp: 4000K (Neutral)
 Color Accuracy: 83 CRI
 L70 Lifespan: 100,000
 Lumens: 2336
 Efficacy: 88 LPW

Technical Specifications

Listings

UL Listing:

Suitable for damp locations. Recommended for indoor use only.

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

Electrical

Drivers:

120 - 277V, 0 - 10V dimming down to 10%, 93.7% power factor, 1 kV surge protection

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims as low as 10%.

Optical

Reflector:

40° reflector

Aperture:

2.5"

Construction

Housing:

Precision extruded aluminum

Lens:

High-transmission, microprismatic acrylic lens for smooth light distribution and uniformity

Finish:

Formulated for high-durability and long lasting color

Green Technology:

Mercury and UV-free. RoHS compliant components.

Mounting:

For direct ceiling and wall mounting

LED Characteristics

LEDs:

Discreet LEDs on PCB board

Lifespan:

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

Color Consistency:

3-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at

Special Order:

Available in 6-8 weeks by special request

Features

Offers a clean flush mount directly to a ceiling or a wall

3-step binning for color consistency

0-10V dimming standard

100,000-Hour LED lifespan

Ordering Matrix

Family	Length	Mounting	Wattage (5W/ft or 10W/ft)	Driver	Optics	Color Temp	Finish	Battery Backup
BOA	6	S	30	D10	40	N	W	^
	2 = 2FT	S =	10 = 2FT 5W/FT	D10 = 0-10V	40 = 40 degrees	N = 4000K Neutral	W = Matte	Blank = No Battery Backup
	4 = 4FT	Surface	20 = 2FT 10W/FT or 4FT	Dimming	reflector	YN = 3500K Warm	White	/E2 = Emergency Battery
	6 = 6FT	P =	5W/FT			Neutral	S = Matte	Backup
	8 = 8FT	Pendant	30 = 6FT 5W/FT			Y = 3000K Warm	Silver	
	10 =		40 = 4FT 10W/FT or 8FT				B = Matte	
	10FT		5W/FT				Black	
	12 =		50 = 10FT 5W/FT					
	12FT		60 = 6FT 10W/FT or 12FT					
			5W/FT					
			80 = 8FT 10W/FT					
			100 = 10FT 10W/FT					
			120 = 12FT 10W/FT					