

Project: Type: Prepared By: Date:



Features and Benefits

Energy efficient replacement for incandescent and halogen reflector lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Frosted lens produces smooth diffuse light

 $Longer\,life span\,compared\,to\,legacy\,equivalents\,minimizes\,replacement\,and\,maintenance\,costs$

ENERGY STAR Compliant

Dimmable with common dimmer types (see Dimmer Compatibility List)

Performance	Beam Angle:	Housing Finish:	
Product Type:	110°	White	
Reflector			
	Electrical	Lens Finish:	
Input Wattage:	Power Factor:	Frosted	
12W	>0.7		
		Installation	
Lumens:	Dimmable:	Base Type:	
1,100lm	Yes, down to 10%	E26 Edison	
Efficacy:	Input Voltage:	Other	
92lm/W	120V	Technology EQ:	
		Incandescent	
L70 Lifespan:	Operating Frequency:		
25,000-Hour LED lifespan based on IES LM-70 results	60 Hz	Warranty (Years):	
Matte as Footbales as	On and in a Tanana and an	3 years	
Wattage Equivalency:	Operating Temperature:		
85	-20°C to 45°C	Compliance	
LED Characteristics	Construction	UL Listed:	
		Yes	
Color Accuracy (CRI):	Bulb Shape:		
80	BR40	Environment:	
		Damp / Enclosed	
Color Temperature:	Enclosure Material:		
3000K	Plastic	Rohs:	
		Mercury and UV free. RoHS-compliant components	



Technical Specifications (continued)

FCC

Complies with Part 15B of the FCC Rules

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
16	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	0	0	0
PALLET	360	0	0	0

