



CL3/0516TN, Copper Lay-in Lug, Tin Plated

By Burndy
Catalog # [CL3/0516TN](#)



COPPER LAY-IN-LUG WIRE RANGE: 3/0 - #6 STEEL SET SCREW TIN PLATED.

Features

- UL486A-B Wire Connectors
- CSA Certified
- Suitable for copper conductors only

General

Catalog Number	CL3/0516TN
Plated	Y
Plating Type	Tin
Trade Name	QIKLUG™
UPC	781810505151
UPC 12 Digit	7818105051511

Dimensions

Dimension - Height inch	1.56 in
Dimension - Hole Size inch	0.33 in
Dimension - Length Overall inch	2.00 in
Dimension - Pad Width inch	0.80 in
Dimension - Width inch	0.80 in

Conductor Related

Conductor - Copper Solid Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG
Conductor - Copper Solid Size Range	6 AWG-3/0 AWG
Conductor - Copper Str Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG
Conductor - Copper Str Size Range	6 AWG - 3/0 AWG

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Logistics

Carton Quantity	90
Minimum Pack Quantity	1

Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_CL_LA](#)
- [Sales Drawings - 30000650](#)
- [Specifications - CL3/0516TN](#)
- [Specifications - BURNDY_CL30516TN_Specsheet](#)