



# KA36229U, #4 Stranded - 600 kcmil conductor for ONE conductor; 1/0 - 250 kcmil range for TWO conductor; dual rated AL9CU, CSA Certified; UL Listed

By Burndy  
Catalog # [KA36229U](#)



#4 Stranded - 600 kcmil conductor for ONE conductor; 1/0 - 250 kcmil range for TWO conductor; dual rated AL9CU, CSA Certified; UL Listed.

## Features

- Dual rated panelboard lugs constructed from high strength extruded aluminum alloy , electro tin-plated to provide low contact resistance

## General

Catalog Number	KA36229U
Connector Type	Terminal
Installation Torque	550 LBS/in
Recommended in-lb	
Material	Aluminum
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Type	Bolted Lugs & Terminals
UPC	781810654514

## Dimensions

Dimension - Bolt Size fraction	3/8
Dimension - D inch	1.50 in
Dimension - Height inch	1.81 in
Dimension - L Length Overall mm	71 mm
Dimension - Length Overall inch	2.81 in
Dimension - N inch	0.63 in
Dimension - Stud Size inch	3/8
Dimension - Width inch	1.38 in
Dimension - Width mm	35 mm

## Conductor Related

Conductor - Copper Str Size	4 Str. - 600 kcmil or (2) 250 kcmil - 1/0 Str.
Conductor - Copper Str Size Range	4 Str. - 600 kcmil or (2) 250 kcmil - 1/0 Str.
Conductor Type	CU C Str-Size

## Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	EX
Status	
UL Listed	Yes

## Logistics

Carton Quantity	60
Minimum Pack Quantity	1

## Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Sales Drawings - 50038316](#)  
[Specifications - KA36229U](#)