



# KAPO750, 750 kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.

By Burndy  
Catalog # [KAPO750](#)

750 kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.



## Application

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

## General

Catalog Number	KAPO750
Connector Type	Offset
EU RoHS Indicator	Contact Manufacturer
Hex Key	1/2 in
Installation Torque	500
Recommended in-lb	
Material	Aluminum
Sub Brand	Pin Adaptor
Type	350 - 750 Mechanical Pin Adaptor; Off-Centered Pin
UPC	621945493377

## Dimensions

Dimension - Strip Length inch	2.30 in
Dimensions	4.46 in x 1.87 in x 2.37 in
Height	2.37 in
Length	4.46 in
Outside Diameter	1.75 in
Width	1.87 in

## Electrical Ratings

Amperage Rating	535 A
-----------------	-------

## Conductor Related

Conductor - AL Str Size Range	350 kcmil - 750 kcmil
Conductor - Copper DLO Size Range	350 kcmil - 750 kcmil
Conductor - Copper Flex H Size Range	350 kcmil - 750 kcmil
Conductor - Copper Flex I Size Range	350 kcmil - 750 kcmil
Conductor - Copper Flex K Size Range	350 kcmil - 750 kcmil
Conductor - Copper Str Size Range	350 kcmil - 750 kcmil
Conductor Size	350-750 KCMIL

## Certifications And Compliance

Buy American Compliant	No
------------------------	----

## Logistics

Carton Quantity	20
Minimum Pack Quantity	1
Pallet Quantity	1000

## Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Sales Drawings - 50076514](#)  
[Specifications - KAPO750](#)



A Hubbell brand