



UCG28R, Parallel Clamp, Aluminum

By Burndy
Catalog # [UCG28R](#)

Parallel Clamp, Cast Aluminium Alloy, 2.20" L, 2.75" Height, 2.20" W.



General

Catalog Number	UCG28R
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Aluminum
Plated	N
Plating Type	Unplated
Trade Name	TAPIT™
UPC	781810111086

Dimensions

Dimension - B Length fraction	2-1/5 in
Dimension - B Length inch	2.20 in
Dimension - Height fraction	2-3/4 in
Dimension - Height inch	2.75 in
Dimension - Width fraction	2-1/5 in
Dimension - Width inch	2.20 in

Conductor Related		Certifications And Compliance	
Conductor - AAAC 5005 Size A	123.3 (7) kcmil;155.4 (7)	Certification - CSA Approved	No
	kcmil;195.7 (7) kcmil;246.9 (7)	Certification - ETL	No
	kcmil;312.8 (19) kcmil;394.5 (19)	Certification - UL Recognized	No
	kcmil	Certification - cULus	No
Conductor - AAAC 5005 Size A Range	123.3 (7) kcmil-394.5 (19) kcmil	Standards - RoHS Compliance Status	CM
Conductor - AAAC 5005 Size B	30.58 (7) kcmil;48.69 (7)	UL Listed	No
	kcmil;77.47 (7) kcmil;123.3 (7)		
	kcmil;155.4 (7) kcmil;195.7 (7)		
	kcmil;246.9 (7) kcmil		
Conductor - AAAC 5005 Size B Range	30.58 (7) kcmil-246.9 (7) kcmil		
Conductor - AAAC 6201 Size A	123.3 (7) kcmil;155.4 (7)		
	kcmil;195.7 (7) kcmil;246.9 (7)		
	kcmil;312.8 (19) kcmil;394.5 (19)		
	kcmil		
Conductor - AAAC 6201 Size A Range	123.3 (7) kcmil-394.5 (19) kcmil		
Conductor - AAAC 6201 Size B	30.58 (7) kcmil;48.69 (7)		
	kcmil;77.47 (7) kcmil;123.3 (7)		
	kcmil;155.4 (7) kcmil;195.7 (7)		
	kcmil;246.9 (7) kcmil		
Conductor - AAAC 6201 Size B Range	123.3 (7) kcmil-394.5 (19) kcmil		
Conductor - AL Str Size A	1/0 AWG;2/0 AWG;3/0		
	AWG;4/0 AWG		
Conductor - AL Str Size A Range	1/0 AWG-4/0 AWG		
Conductor - AL Str Size B	1/0 AWG;2/0 AWG;3/0		
	AWG;4/0 AWG		
Conductor - AL Str Size B Range	1/0 AWG-4/0 AWG		
Conductor - Copper Str Size A	1/0 ;2/0 AWG;3/0 AWG;4/0		
	AWG		
Conductor - Copper Str Size A Range	1/0 -4/0 AWG		
Conductor - Copper Str Size B	1/0 ;2/0 AWG;3/0 AWG;4/0		
	AWG		
Conductor - Copper Str Size B Range	1/0 -4/0 AWG		
Conductor Type	• AL C Str-Size A		
	• CU C Solid-Size A		
	• CU C Str-Size A		
	• AAAC C 5005-Size A		
	• AAAC C 6201-Size A		
	• AL C Str-Size B		
	• CU C Solid-Size B		
	• CU C Str-Size B		
	• AAAC C 5005-Size B		
	• AAAC C 6201-Size B		