

Y3126R, Compression Splice Reducer, Barrel A 350 kcmil, Barrel B 2/0 AWG

By Burndy Catalog # Y3126R

350 kcmil CU Long Barrel Size Reduced Down To 2/0 AWG Wire Size, Internal Chamfer, Tin Plated, Up to 35kV, RED Color Code, 18 or 324 Die Index.



Copper reducing sleeve that allows a larger terminal or splice to accommodate a smaller wire gauge

Application

Wire Reducing Splice Adapter Insert

General

Catalog Number Y3126R
Color Code Red

Connector Type LONG BARREL

Die Index 18
Feature - Barrel Type Long
Finish Type Tin-Plated
Material COPPER

Plated Y

Plating Type Tin - Electro Plated

Temperature Rating 194

UPC 781810102374 UPC 12 Digit 7818101023744

Dimensions

Dimension - B Length inch 2.00 in Dimension - L Length Overall 51 mm

mm

Dimension - Length Overall 2.00 in

inch

Dimension - Outside Diameter 0.687 in

inch

Electrical Ratings

Voltage - Maximum 35000



Conductor Related

Conductor - Copper Str Run	350 kcmil
Conductor - Copper Str Run	350 kcmil
Range	
Conductor - Copper Str Size	2/0 AWG
Range	
Conductor - Copper Str Tap	2/0 AWG
Conductor - Copper Str Tap	2/0 AWG
Range	
Conductor - Material	COPPER
Conductor Type	CODE
Wire Size	#2/0 AWG

Certifications And Compliance

Certification - CSA Approved	l No
Certification - ETL	No
Certification - UL Recognized	l No
Certification - cULus	No
Standards - RoHS Compliance	e CM
Status	
UL Listed	No

Logistics

Carton Quantity	75
Minimum Pack Quantity	20
Pallet Quantity	13050

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section C - Compression Connections

Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - SD..016040-01

