

YA30L45, Compression Terminal, 300 kcmil Cu, 1-Hole, 1/4" Stud, Standard Barrel, 45 Degree

By Burndy Catalog # YA30L45

Copper Compression Lug, 1 Hole w/ Inspection Window, 300 kcmil, 1/4" Stud, Short Barrel, White, Tin Plated.

Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

General

Catalog Number	YA30L45
Color Code	White
Connector Type	STANDARD BARREL
Die Index	17
Feature - Barrel Style	 Chamfered
	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of	1
Holes	
Plated	Υ
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Туре	Standard Barrel, Tin Plated
UPC	781810314135



Dimensions

Dimension - B Length fraction	1 in
Dimension - B Length inch	1.03 in
Dimension - Bolt Hole Size inch	0.52 in
Dimension - Bolt Size fraction	1/2
Dimension - Bolt Size inch	0.5
Dimension - D inch	1.08 in
Dimension - Height inch	1.75 in
Dimension - Hole Size mm	13 mm
Dimension - L Length Overall	66 mm
mm	
Dimension - Length Overall	2.60 in
inch	
Dimension - N inch	0.53 in
Dimension - Outside Diameter	0.81 in
inch	
Dimension - Pad Width inch	1.20 in
Dimension - Strip Length inch	1 in
Dimension - Stud Size inch	1/2
Dimension - Z (inch)	0.55 in
Physical Attribute - Tongue	45 Degree
Angle	

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper DLO Size	N/A
Range	
Conductor - Copper Str Navy	300 (91) Navy
Size	
Conductor - Copper Str Navy	300 (91) Navy
Size Range	
Conductor - Copper Str Size	300 KCMIL
Conductor - Copper Str Size	300 kcmil
Range	
Conductor - Material	COPPER
Conductor Size	300 KCMIL
Conductor Type	CODE

Certifications And Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) UL 486A-486B

Standards - Industry Standards UL467

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 10
Minimum Pack Quantity 10
Pallet Quantity 9600

Product Assets

3D Models - YA30L45_MODEL-PDF 3D Models - YA30L45_MODEL-STEP 3D Models - YA30L45_MODEL-IGES

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - SE..209240-22

Video - HYDENT Compression Terminal Overview Video



©2024 Hubbell Incorporated. All rights reserved BRDY-YA30L45-SPEC-EN | REV 8/2024