

YCHC39TC31, Compression C-Tap

By Burndy Catalog # YCHC39TC31

Copper Compression C Tap, 750-500 kcmil (Main), 350 kcmil-2 AWG (Tap 1), 2-6 AWG (Tap 2), 8-14 AWG (Tap 3), Tin Plated.



Application

Wire Tap

General

Plated

YCHC39TC31 Catalog Number Color Code Blue C-TAP Connector Type 1103 Die Index EU RoHS Indicator Yes Tin-Plated Finish Type Material COPPER

Tin - Electro Plated Plating Type

Sub Brand CRIMPIT Trade Name CRIMPIT™ Type YCHC Series **UPC** 781810013786 7818100137866 UPC 12 Digit

Dimensions

inch

Dimension - Height inch 2.96 in Dimension - L Length Overall 33 mm mm Dimension - Length Overall 1.31 in

Dimension - Strip Length inch 1-3/8 Dimension - Width inch 1.53 in

Electrical Ratings

Voltage - Maximum 35000

Conductor Related

Conductor - Copper Flex I Run 500 kcmil

Range

Conductor - Copper Flex K Run 500 kcmil

Range

Conductor - Copper Flex M Run 500 kcmil

Range

750 KCMIL-350 KCMIL Conductor - Copper Str Run 750 KCMIL-350 KCMIL

Conductor - Copper Str Run

Range

350 KCMIL-2 AWG Conductor - Copper Str Tap Conductor - Copper Str Tap 350 KCMIL-2 AWG

Range

Conductor - Material COPPER

Conductor Size 750 KCMIL-350 KCMIL

Conductor Type CODE/FLEX

Certifications And Compliance

Buy American Compliant Certification - CSA Approved Yes Certification - ETL Certification - UL Recognized Nο Certification - cULus

UL 486A-486B Industry Standard(s)

Standards - RoHS Compliance СМ

Status

UL Listed Yes

Logistics

Carton Quantity 25 25 Minimum Pack Quantity Pallet Quantity 2400

Product Assets

3D Models - YCHC39TC31_MODEL-STEP

3D Models - YCHC39TC31_MODEL-PDF

3D Models - YCHC39TC31_MODEL-IGES

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Catalogs - BURNDY Master Catalog - Section C - Compression

Connections

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - SD..206624-01

Specifications - YCHC39TC31



©2024 Hubbell Incorporated. All rights reserved BRDY-YCHC39TC31-SPEC-EN | REV 8/2024