

Substation - Copper Terminal

By Burndy
Catalog # [NAS4034N](#)

Cast Cu Alloy Reversible Cap Terminal, Bolted, 2/0 Str - 800 kcmil Cu Cable, 4-NEMA Pad Holes, Silicon Bronze H/W, .56" Hole Dia, 5.88 L, 0.31 T, 2.44 W.



Application

Substation

General

Catalog Number	NAS4034N
Clamping Element Design	Body And Cap
Connector Type	Terminal
Material	Copper Alloy
Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Y
Physical Attribute - Number of Holes	4
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Pad Configuration	3 x 3 - 4 holes
Physical Attribute - Pad Orientation	Straight
Plated	N
Plating Type	Unplated
UPC	781810002865
UPC 12 Digit	7818100028655

Dimensions

Dimension - B Length fraction	2-31/50 in
Dimension - B Length inch	2.62 in
Dimension - D inch	3.00 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Height fraction	2-3/10 in
Dimension - Height inch	2.30 in
Dimension - Hole Size fraction	9/16
Dimension - L Length Overall mm	149 mm
Dimension - Length Overall inch	5.88 in
Dimension - N inch	0.62 in
Dimension - Pad Width inch	3.00 in
Dimension - Width fraction	2-11/25 in
Dimension - Width inch	2.44 in
Dimension - Width mm	62 mm

Conductor Related

Conductor - Connection Combination	Cable to Flat
Conductor - Copper Solid Size	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	2/0 AWG-4/0 AWG
Conductor - Copper Str Size	2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil;700 kcmil;750 kcmil;800 kcmil
Conductor - Copper Str Size Range	2/0 AWG-800 kcmil
Conductor - Large Groove Max	800 kcmil
Conductor - Large Groove Min	500 kcmil
Conductor - Small Groove Max	500 kcmil
Conductor - Small Groove Min	2/0 str
Conductor Type	- CU C Str-Size - CU C Solid-Size
Number of Conductors	1

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Product Assets

[3D Models - NAS4034N_MODEL-IGES](#)
[3D Models - NAS4034N_MODEL-STEP](#)
[3D Models - NAS4034N_MODEL-PDF](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Catalogs - Section L - Bolted Substation](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_NAS_LineArt](#)
[Sales Drawings - SE079584-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY_CA-NAS4034N-SPEC-EN | REV 6/2024