

BTH250GPSQ



Metal Halide HID with temporary guard.

Color: N/A

Weight: 21.1 lbs

Project:

Type:

Prepared By:

Date:

Lamp Info

Type: BT28
Watts: 250W
Shape/Size: N/A
Base: N/A
ANSI: N/A
Hours: 15,000
Lamp Lumens: 23,800
Efficacy: 86 LPW

Ballast Info

Type: CWA HPF QT
120V: 1.4/2.5A
208V: .8/1.5A
240V: .7/1.3A
277V: .6/1.1A
Input Watts: 278W
Efficiency: 90%

Technical Specifications

Listings

UL Listing:

Suitable for damp locations

Construction

Housing:

Die cast aluminum housing and wiring box with 1/2" NPS knockouts and easy leveling adjustment. Comes with 3' cord, hook/loop and safety chain.

Mounting Box:

Die-cast aluminum mounting box tapped for 3/4" conduit.

Electrical

Ballast:

Quad-Tap CWA Ballast (120/208/240/277 Volt).

Watts:

250 Watt.

2005 NEC Compliance:

Open rated lamp and socket comply with 2005 NEC code .

Optical

Lamp:

Mogul Base Up BT28 Metal Halide lamp supplied.

Features

Rugged hook/loop with 3' cord or easy installation

Heavy duty die cast housing

Pulse rated Mogul Base Socket for open rated lamps