



GP1726G1

by Burndy
Catalog ID: GP1726G1

Prop 65 Notice

BURNDY® Rod or Pipe; UL467, UL Listed-Direct Burial, RoHS Compatible with Exemption; Conductor Range (Main/Primary): 2 IN Tubing(Round); Conductor Range (Tap/Secondary): #6 Sol - 2/0 Str Cu Conductors

Product Details

General

Installation Torque Recommended in-lb	240 LBS/in
Material	Copper Alloy, Cast
Material Type - Screw	DURIUM™ Silicon Bronze
Pedestal Type	Round
Plated	N
Plating Type	Unplated
U Bolt Type	UB268
UPC	781810468142
UPC 12 Digit	7818104681422

Dimensions

Bolt Size	3/8 in
Dimension - B Length inch	2.12 in
Dimension - L Length Overall mm	38 mm
Dimension - Length Overall inch	1.50 in
Dimension - Width fraction	3-2/9 in
Dimension - Width inch	3.22 in
Dimension - Width mm	82 mm

Conductor Related

Conductor Size	#6 AWG Sol - 2/0 AWG Str
----------------	--------------------------

Certifications and Compliance

Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)