

DSD-SR

Horsepower Rated 30 A, 600 V
Selector Switch Front Operated

Class I, Groups C & D
Class II, Groups E, F & G
Class III
Enclosure 3, 5 & 12

4C

4C
Control Stations

Ordering Information

Switch Function	Catalog Number	Number of Poles	Number of Positions	Connecting Diagram	
ON/OFF	DSD-SR30120	1	2		1-6 Pole
	DSD-SR30220	2	2		
	DSD-SR30320	3	2		
	DSD-SR30420	4	2		
	DSD-SR30520	5	2		
	DSD-SR30620	6	2		
DOUBLE-THROW without OFF	DSD-SR30121	1	2		1-3 Pole
	DSD-SR30221	2	2		
	DSD-SR30321	3	2		
DOUBLE-THROW without OFF with electrically isolated contacts	DSD-SR30123	1	2		1-3 Pole
	DSD-SR30223	2	2		
	DSD-SR30323	3	2		
DOUBLE-THROW with OFF	DSD-SR30132	1	3		1-3 Pole
	DSD-SR30232	2	3		
	DSD-SR30332	3	3		
DOUBLE-THROW with OFF and electrically isolated contacts	DSD-SR30134	1	3		1-3 Pole
	DSD-SR30234	2	3		
	DSD-SR30334	3	3		

Electrical Specification

Voltage	Horsepower Rating	
	3PH	1PH
120	3	1.5
240	7.5	3
480	10	5
600	10	5

Maximum Current: 30 A
Heavy-duty A600 rating

Options

Lockout for 2 position switch,
handle in either position . . . SX178

Lockout for 3 position switch,
handle in either position . . . S349



DSD-SR cover assembly shown mounted to an EDS back box