



Color: White

Weight: 2.2 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	16W
120V	0.15A	Color Temp	2700/3000/3500/4000/5000K
208V	0.09A	Color Accuracy	90 CRI
240V	0.07A	L70 Lifespan	50,000 Hours
277V	0.06A	Lumens	1,150 lm
Input Watts	16W	Efficacy	72

Technical Specifications			
Performance		Electrical	
Product Type: Flush Mount		Driver: Constant Current, Class 2	
Description: 5-CCT selectable, back-lit LED retrofit fixture. Installs on standard junction boxes. Dimmable models available for 0-10V or TRIAC dimming systems with optional microwave sensor and/or integrated emergency battery backup.		THD: ≤20%	
Wattage Equivalency: 75W Incandescent		Power Factor: ≥0.9	
Input Wattage: 16W		Dimmable: Yes, dimmable down to 10% on compatible 0-10V dimming systems. See Dimmer Compatibility List. Requires separate 0-10V DC dimming circuit.	
Nominal Lumens: 1,150lm		Input Voltage: 120-277V	
Efficacy: 72lm/W		Operating Frequency: 50/60Hz	
Measured Lumens: 1161lm @ 2700K; 1258lm @ 3000K; 1305lm @ 3500K; 1308lm @ 4000K; 1235lm @ 5000K		Input Current @ 120V (mA): 150mA	
Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results		Input Current @ 208V (mA): 85mA	
		Input Current @ 240V (mA): 73mA	
		Input Current @ 277V (mA): 63mA	
		Operating Temperature: -4°F to 104°F (-20°C to 40°C)	
		Sensor Settings	
		Sensor Connection Type: Integrated, behind the lens	
		Max Mounting Height: 9 ft	
		Detection Range: 20 ft diameter at 9 ft mounting height	
		Sensor Technology: Microwave (MVS)	
		Default Setting: 30 second timeout	
		Adjustable Sensor Settings?: Yes, using MSR1 remote.	
		Sensing Type: Occupancy, Vacancy	
		Occupied Actions: On at 100% dim level	

Technical Specifications (continued)

Vacant Actions:
Off

Occupancy Timeout:
30 seconds

LED Characteristics

Beam Angle:
120°

Color Temperature:
Field adjustable via dip switch
2700/3000/3500/4000/5000K

Color Accuracy (CRI):
90 CRI

R9 Value:
High color performance with R9 greater than 50

Color Consistency:
<4-step (2700K & 5000K); <7-step
(3000K/3500K/4000K) MacAdam Ellipse binning to
achieve consistent fixture-to-fixture color

Color Stability:
LED color temperature is warrantied to shift no more
than 200K in color temperature over a 5-year period

Color Uniformity:
RAB's range of Correlated Color Temperature follows
the guidelines of the American National Standard for
Specifications for the Chromaticity of Solid State
Lighting (SSL) Products, ANSI C78.377-2017.

Installation

Mounting:
Surface mount

Construction

Size:
11"

Shape:
Round

Finish:
White

Enclosure Material:
Plastic

Trim Style:
Smooth

Lens Finish:
Frosted

Lens:
Polycarbonate light diffuser distributes light evenly
and smoothly for general lighting applications

Compliance
Listings:
UL Listed

Environment:
Suitable for use indoors and outdoors in dry, damp,
or wet environments.

IC Rated:
No

Air Tight:
No

Energy Star Approved:
This product is ENERGY STAR® Certified.

DLC Listed:
No

Certification Model Number:
DLS0099(CRVFAS-11R-16-9CCT-UNV-W/MVS)

California Title 20 Compliant:
Can be used to conform with the requirements of
California Title 20

California Title 24 JA8 Compliant:
Can be used to conform with the requirements of
California Title 24 Part 6

California Energy Commission (CEC) Status:
Lawful for Sales in California

NEC Compliant:
Suitable for use in closets. Compliant with NEC Sec.
410.16 (A)(1) and 410.16 (C1).

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been
tested by an independent laboratory in accordance
with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15 of the FCC Rules


Trade Agreements Act Compliant:
This product is a product of Cambodia and a
"designated country" end product that complies
with the Trade Agreements Act

Other

Compatible Accessories:
CRVFA-CONVERTIBLE-KIT
Pendant mount kit for CRVFA

Warranty:
RAB warrants that our LED products will be free from
defects in materials and workmanship for a period of
five (5) years from the date of delivery to the end
user, including coverage of light output, color
stability, driver performance and fixture finish. RAB's
warranty is subject to all terms and conditions found
at rablighting.com/warranty.


Dimensions




Features

- Surface mount to ceiling or wall
- Field-adjustable "set and forget" color temperature
- Diffused lens provides soft, smooth light
- Ideal for hospitality and multi-family residential applications
- Suitable for wet and damp locations

Coverage Pattern



Ceiling Mount



Wall Mount

Ordering Matrix

Family	Type	Size	Wattage	CRI/Color Temp	Driver	Finish	Sensor	Battery Backup
CRVFA	S	11	R	16	9CCT	UNV	W	/MVS
	S = Smooth	11 = 11" 19 = 19" 18 = 18" 14 = 14" 12 = 12" R = Round	16 = 16W 20 = 20W 32 = 32W	9CCT = 90 CRI, 2700/3000/3500/4000/5000K CCT Adjustable	UNV = 120-277V, 0-10V Dimming UNVT = 120-277V, TRIAC/ELV	W = White BN = Brushed Nickel	Blank = No Option /MVS = Microwave Occupancy Sensor	Blank = No Option /EM = Emergency Battery Backup /EMBB = Emergency Battery Backup