

FEATURES & SPECIFICATIONS

INTENDED USE — The FS Series recessed LED luminaire combines modern aesthetics and performance in a general lighting product that enables the transformation from fluorescent to LED. The high efficacy light engine delivers long life and excellent color to ensure a quality lighting installation. Integrated controls options provide for design flexibility and optimum energy savings. Multiple lumen packages and driver options provide solutions for all your lighting applications.

Certain airborne contaminants can diminish integrity of acrylic. [Click here for Acrylic Environmental Compatibility table for suitable uses.](#)

CONSTRUCTION — Rugged, one-piece cold-rolled steel coated polyester, painted after fabrication. The satin white lens provides excellent shielding and wide distribution. End plates include integral T-bar clips. Fixture may be mounted and wired in continuous rows. Total fixture height is only 4-3/8".

ELECTRICAL — Long-life LEDs, coupled with high-efficiency drivers, provide superior illumination for extended service life. 90% LED lumen maintenance at 60,000 hours (L90/60,000). The LEDs have a CRI of 82. eldoLED driver options deliver choice of dimming range, and choices for control, while assuring flicker-free, low-current inrush, 89% efficiency and low EMI.

Optional integrated nLight® controls make each luminaire addressable - allowing it to digitally communicate with other nLight enabled controls such as dimmers, switches, occupancy sensors and photocontrols. Simply connect all the nLight enabled control devices and the FSL luminaires using standard CAT-5 cabling. Unique plug-and-play convenience allows devices and luminaires to automatically discover each other and self-commission.

Lumen Management: Unique lumen management system (option N80) provides onboard intelligence that actively manages the LED light source so that constant lumen output is maintained over the system life, preventing the energy waste created by the traditional practice of over-lighting.

Step-level dimming option allows system to be switched to 50% power for compliance with common energy codes while maintaining fixture appearance.

Driver disconnect provided where required to comply with US and Canadian codes.

INSTALLATION — Unique grid interfacing arrangement provides mounting into standard 1" and 9/16" tee bar or screw slot grids. 9/16" allows fixture trim to hang level with architectural ceiling tiles. Drywall ceiling adaptors available. Suitable for damp location.

LISTINGS — CSA certified to meet US and Canadian standards. IC rated. DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC Premium qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY — 5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

| |
|----------------|
| Catalog Number |
| Notes |
| Type |



FS Series

2FSL4

2' x 4'
LED



eldoLED



Stock Configurations

2FSL4 40L E21 LP835
2FSL4 40L E21 LP840

Capable Luminaire


This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and out-of-the-box control compatibility with simple commissioning.

- All configurations of this luminaire meet the Acuity Brands' specification for chromatic consistency
- This luminaire is part of an A+ Certified solution for nLight® control networks when ordered with drivers marked by a **shaded background***
- This luminaire is part of an A+ Certified solution for nLight control networks, providing advanced control functionality at the luminaire level, when selection includes driver and control options marked by a **shaded background***

To learn more about A+, visit www.acuitybrands.com/aplus.

*See ordering tree for details

2FSL4 LED Recessed Lighting 2'x4'



A+ Capable options indicated by this color background.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: 2FSL4 40L EZ1 LP835 N100

| 2FSL4 | | | | | | | | | | | | | | | | |
|---------------|----------------------------------|-----------------------|---------------------|---------------------------------------|------|---------------------------------------|--------------|---|--|--|--|--|-----------------------|--|---------|--|
| Series | Air function | | Lumens | | Lens | | Voltage | | Driver | | Color temperature | | Controls ⁵ | | Options | |
| 2FSL4 2X4 FSL | (blank) Static H Heat removal | 30L 3000 ¹ | (blank) Satin white | (blank) MVOLT 347 347 ² | EZ1 | eldoLED dims to 1%, 0-10V | LP830 3000 K | (blank) No controls | EL7L | 700 lumen battery pack | | | | | | |
| | | 40L 4000 ¹ | | | EZB | eldoLED dims to black, 0-10V | LP835 3500 K | N80 | nlight® with 80% lumen management | EL14L | 1400 lumen battery pack | | | | | |
| | | 48L 4800 ¹ | | | EDB | eldoLED DALI ³ | LP840 4000 K | N80EMG | nlight® with 80% lumen management. For use with generator supply EM power. | CP | Chicago plenum | | | | | |
| | | 60L 6000 ¹ | | | EXB | eldoLED DMX/RDM ³ | LP850 5000 K | N100 | nlight® without lumen management | PWS1836 | 6' prewire, 3/8" diameter, 18-gauge, 1-circuit | | | | | |
| | | 72L 7200 ¹ | | | SLD | Step-level dimming ^{3,4} | N100EMG | nlight® without lumen management. For use with generator supply EM power. | PWS1846 | 6' prewire, 3/8" diameter, 18-gauge, 2-circuit | | | | | | |
| | | | | | EXA1 | Dims to 1%, XPoint wireless enabled | | | RRL__ | RELOC®-ready luminaire ⁶ | | | | | | |
| | | | | | EXAB | Dims to dark, XPoint wireless enabled | | | NPLT | Narrow pallet | | | | | | |
| | | | | | EOHN | On/Off (non-dim) | | | | | | | | | | |

| Accessories: Order as separate catalog number. | |
|--|---|
| 2FS4 F916 | Trim to adjust fixture mounting flush with 9/16" T-bar; for 2x4 fixture |
| DGA24 FS/VT | Drywall ceiling adaptor , unit installation |


- Notes
- 1 Approximate lumen output.
 - 2 Consult factory for availability. Not available with SLD, EL7L, or EL14L.
 - 3 Not available with N80, N80EMG, N100 or N100EMG.
 - 4 When using prewire option, use PWS1846.
 - 5 nIO access limitations on 30L or EZB.
 - 6 For ordering logic consult: [RRL_2013](#).

2FSL4 LED Recessed Lighting 2'x4'


| Performance Data | | | |
|------------------|--------------------------|--------|-----|
| Lumen package | Input watts ¹ | Lumens | LPW |
| 30L LP830 | 30.7 | 3170 | 103 |
| 30L LP835 | 30.8 | 3341 | 108 |
| 30L LP840 | 30.9 | 3430 | 111 |
| 30L LP850 | 31.0 | 3664 | 118 |
| 40L LP830 | 39.2 | 3994 | 102 |
| 40L LP835 | 39.4 | 4247 | 108 |
| 40L LP840 | 39.5 | 4368 | 111 |
| 40L LP850 | 39.6 | 4637 | 117 |
| 48L LP830 | 46.2 | 4596 | 100 |
| 48L LP835 | 46.4 | 4856 | 105 |
| 48L LP840 | 46.6 | 4995 | 107 |
| 48L LP850 | 46.7 | 5347 | 115 |
| 60L LP830 | 52.0 | 5071 | 98 |
| 60L LP835 | 52.2 | 5373 | 103 |
| 60L LP840 | 52.4 | 5531 | 106 |
| 60L LP850 | 52.5 | 5867 | 112 |
| 72L LP830 | 69.5 | 6758 | 97 |
| 72L LP835 | 70.0 | 6847 | 98 |
| 72L LP840 | 70.2 | 7433 | 106 |
| 72L LP850 | 70.3 | 7823 | 111 |

PHOTOMETRICS

2FSL4 40L LP835, test no. LTL24699P5, tested in accordance to IESNA LM-79




2FSL4 48L LP835, test no. LTL24699P9, tested in accordance to IESNA LM-79



2FSL4 LED Recessed Lighting 2'x4'


MOUNTING DATA



DIMENSIONS

All dimensions are inches (centimeters) unless otherwise specified.



| Specifications |
|---------------------|
| Length: 48 (122.0) |
| Width: 24 (61.0) |
| Depth: 4-3/8 (11.1) |



| nLight® Control Accessories: <i>Order as separate catalog number. Visit www.sensorswitch.com/nLight for complete listing of nLight controls.</i> | | | |
|--|---------------------|--|-----------------------------|
| WallPod stations | Model number | Occupancy sensors | Model number |
| On/Off | nPODM [color] | Small motion 360°, ceiling (PIR / dual tech) | nCM 9 / nCM PDT 9 |
| On/Off & Raise/Lower | nPODM DX [color] | Large motion 360°, ceiling (PIR / dual tech) | nCM 10 / nCM PDT 10 |
| Graphic Touchscreen | nPOD GFX [color] | Wide view (PIR / dual tech) | nWV 16 / nWV PDT 16 |
| Photocell controls | Model number | Wall Switch w/ Raise/Lower (PIR / dual tech) | nWSX LV DX / nWSX PDT LV DX |
| On/Off & Dimming | nCM ADCX | Cat-5 cables (plenum rated) | Model number |
| | | 10', CAT5 10FT | CAT5 10FT J1 |
| | | 15', CAT5 15FT | CAT5 15FT J1 |

Constant Lumen Management

Enabled by the embedded nLight control, the FSL actively tracks its run-time and manages its light source such that constant lumen output is maintained over the system life. Referred to as lumen management, this feature eliminates the energy waste created by the traditional practice of over-lighting.



Notes

With nlight 80% lumen management input watts start at 37 and gradually increasing to 46 at 50,000 hrs when using 48L system.