

CLICKTIGHT™ LED TAPE LIGHT CONNECTORS

SPECIFICATION SHEET

The following CLICKTIGHT LED tape light connectors may be utilized in indoor environments. Connectors, extensions cables, etc. are not rated for in-wall installations. All products listed below may not be used with wet location strip light.

Compatible fixtures:

- FLUID VIEW® 12V LED Tape Light
- BLAZE™ 12V LED Tape Light
- AVENUE 24™ 24V Premium LED Tape Light
- ULTRA BLAZE™ 12V & 24V LED Tape Light

- VALENT™ 12V Premium LED Tape Light
- DAZZLE 24™ 24V RGB LED Tape Light
- DAZZLE 24™ 24V RGBW LED Tape Light
- K-RANGE 24® 24V Tunable White LED Tape Light

FLUID VIEW / BLAZ	Item Name	Description			
DI-0850-**	Standard DC Plug Connector	Attaches tape light directly to plug-in adapter / DC plug accessory. 3 x 0.50 x 0.20 in. (L x W x H)	(
DI-0855-** (3 in.) DI-0856-** (24 in.) DI-0857-** (48 in.)	Standard Splice Connection	Attaches tape light directly to a hard-wired driver / low voltage control. 3 ~ 48 x 0.50 x 0.20 in. (L x W x H)	© 0 0 0 0 0		
DI-0860-** (3 in.) DI-0896-** (6 in.) DI-0897-** (12 in.) DI-0861-** (24 in.) DI-0862-** (48 in.)	Standard Flexible Extension	Attaches two sections of tape light together. Wire lead allows for turns around tight corners. $3 \sim 48 \times 0.50 \times 0.20$ in. (L x W x H)			
DI-0865-**	Standard Tape Link	Attaches two sections of tape light together. 0.60 x 0.50 x 0.20 in. (L x W x H)	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□<		
ULTRA BLAZE					
Product #*	Item Name	Description			
DI-0870-**					
	ULTRA BLAZE DC Plug Connector	Attaches tape light directly to plug-in adapter / DC plug accessory. 3 x 0.55 x 0.20 in. (L x W x H)	0 0		
DI-0875-** (3 in.) DI-0876-** (24 in.) DI-0877-** (48 in.)					
DI-0875-** (3 in.) DI-0876-** (24 in.)	Connector ULTRA BLAZE Splice	accessory. $3 \times 0.55 \times 0.20$ in. (L x W x H) Attaches tape light directly to a hard-wired driver / low			

^{*} All wet location accessories have a Class 2 amp rating: 60W/5A @ 12VDC; 100W/4.17A @ 24VDC.

SS050515-1.2

^{**} Products available in 25x and 50x pack bulk quantities. Add -25 or -50 to each product # for bulk quantities.



CLICKTIGHT™ LED TAPE LIGHT CONNECTORS

SPECIFICATION SHEET

DAZZLE 24 RGB Product #*	Item Name	Description	
T T O W O C T	item itame		
DI-0885-** (3 in.) DI-0886-** (24 in.) DI-0887-** (48 in.)	RGB Splice Connector	Attaches RGB tape light directly to an RGB controller or DMX decoder. $3 \sim 48 \times 0.55 \times 0.20$ in. (L x W x H)	
DI-0890-** (3 in.) DI-1090-** (6 in.) DI-1091-** (12 in.) DI-0891-** (24 in.) DI-0892-** (48 in.)	RGB Flexible Extension	Attaches two sections of RGB tape light together. Wire lead allows for turns around tight corners. $3 \sim 48 \times 0.55 \times 0.20$ in. (L x W x H)	
DI-0895-**	RGB Tape Link	Attaches two sections of RGB tape light together. 0.60 x 0.55 x 0.20 in. (L x W x H)	DDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD<l< td=""></l<>
DAZZLE 24 RGBW			
Product #*	Item Name	Description	
DI-RGBW-CKT3-SPLE-** (3 in.) DI-RGBW-CKT24-SPLE-** (24 in.)	RGBW Splice Connector	Attaches RGBW tape light directly to an RGBW controller or DMX decoder. 3 ~ 24 x 0.75 x 0.20 in. (L x W x H)	
DI-RGBW-CKT3-EXT-** (3 in.) DI-RGBW-CKT24-EXT-** (24 in.)	RGBW Flexible Extension	Attaches two sections of RGBW tape light together. Wire lead allows for turns around tight corners. 3 ~ 24 x 0.75 x 0.20 in. (L x W x H)	
DI-RGBW-CKT-LNK-**	RGBW Tape Link	Attaches two sections of RGBW tape light together. $0.60 \times 0.75 \times 0.20$ in. (L x W x H)	# #F
K-RANGE 24			
Product #*	Item Name	Description	
DI-KRNG-CKT3-SPLE-** (3 in.) DI-KRNG-CKT24-SPLE-** (24 in.)	K-RANGE Splice Connector	Attaches K-RANGE tape light directly to a K-RANGE controller. 3 ~ 24 x 0.50 x 0.20 in. (L x W x H)	
DI-KRNG-CKT3-EXT-** (3 in.) DI-KRNG-CKT24-EXT-** (24 in.)	K-RANGE Flexible Extension	Attaches two sections of K-RANGE tape light together. Wire lead allows for turns around tight corners. $3 \sim 24 \times 0.50 \times 0.20$ in. (L x W x H)	
DI-KRNG-CKT-LNK-**	K-RANGE Tape Link	Attaches two sections of K-RANGE tape light together. 0.60 x 0.50 x 0.20 in. (L x W x H)	⊕ ⊕ □ ©

^{*} All wet location accessories have a Class 2 amp rating: 60W/5A @ 12VDC; 100W/4.17A @ 24VDC.

SS050515-1.2

^{**} Products available in 25x and 50x pack bulk quantities. Add-25 or-50 to each product # for bulk quantities.