

DMX WALL MOUNT ZONE CONTROLLER


INSTALLATION GUIDE

SAFETY & WARNINGS

1. Install in accordance with national and local electrical code regulations.
2. This product is intended to be installed and serviced by a qualified, licensed electrician.
3. DO NOT connect directly to high voltage power. Install with a compatible Class 2 constant voltage LED driver (power supply).
4. Only install compatible 12V and 24VDC constant voltage luminaires.
5. This product is rated for indoor installation and is not protected against moisture.
6. Do not modify product beyond instructions or warranty will be void.

QUICK SPECS / MODELS



DI-DMX-WIFI-WMUS-3Z-WH



Input Voltage	12 - 24VDC Constant Voltage
Output Signal	DMX512
WiFi Transmitting Distance	40 ft.



TOOLS FOR INSTALL

Phillips-head screwdriver Flat-head screwdriver



Mini flat-head screwdriver

Wire stripper




INSTALLATION

1 TURN POWER OFF AT CIRCUIT BREAKER





SHOCK HAZARD! May result in serious injury or death.
Turn power OFF at circuit breaker prior to installation.



2 DETERMINE LOCATION TO INSTALL COMPONENTS

See **SYSTEM DIAGRAM** for more information. DMX luminaires can be connected directly to controller. DMX Decoders are only utilized to control Non-DMX type luminaires.



LED Driver

Controller


DMX Decoder

Luminaire

3 CONNECT COMPONENTS

Only use copper wiring. Reference **WIRING CONNECTIONS** and **SYSTEM DIAGRAM** further in this guide for visuals.

4 TURN POWER ON AT CIRCUIT BREAKER



If system remains unresponsive or is working improperly, turn OFF main power at breaker and verify all connections.

INSTALLATION CONT.

Power Indicator

Red indicates unit is OFF.
Blue indicates unit is ON.
Blue flash indicates DATA is transmitting.

Color Wheel

Adjust RGB color mixing.

Power

Short press to turn ALL zones and channels ON/OFF.

RGB Brightness

Long press to adjust brightness of RGB colors simultaneously (7 steps of brightness). Adjust W (4CH) channel separately to adjust tone.

R, G, B, W Channel Adjustment



Short press to turn channel ON/OFF.
Long press to adjust brightness.

RGB 'White' Presets


Short press for 3 types of 'White' RGB presets: warm white, neutral white, cool white. Useful for applications that don't utilize W (CH4) for RGBW applications.

Dynamic Mode

Short press changes mode/pauses mode. Long press adjusts speed of dynamic mode. See 'Dynamic Mode Chart' for mode descriptions.


Zone Control

Short press to control zones 1, 2, or 3.
Long press to turn individual zone ON/OFF.



MOBILE DEVICE OPERATION

The DMX controller can also be controlled remotely via WiFi with a compatible IOS/Android mobile device. Go to iOS or Google Play App Store. Search for "EasyColor Pro" and download application.



PAIRING CONTROLLER TO MOBILE DEVICE


1. Go to WiFi settings of mobile device.
2. Connect to WiFi Network 'EasyLighting'.
3. Type in Password '0123456789'.
4. Open EasyColor Pro Application.

For further operating instructions see 'DMX Wall Mount Mobile Application' Operation Guide at www.DiodeLED.com.


WIRING CONNECTIONS

DO NOT connect directly to 120VAC.


See 'System Diagram' for a general system design.



MOUNTING



Pop off faceplate with a flathead screwdriver.



Mount to a standard switchbox.

SETTING DMX ADDRESS

Each DMX decoder or DMX luminaire needs to be addressed correctly so the controller can distinguish between each decoder. To pair a DMX decoder or luminaire to a specific zone of the controller (1-3), set each decoder/luminaire to one of the following addresses:

- Zone 1: Set to address ‘001’ (will be fixed to address 001 – 004)
- Zone 2: Set to address ‘005’ (will be fixed to address 005 – 008)
- Zone 3: Set to address ‘009’ (will be fixed to address 009 – 012)

Each zone of the controller is fixed with 4 DMX addresses to control the 4 channels:

CH1 – Red, CH2 – Green, CH3 – Blue, CH4 – White or X.


Once DMX address is set on luminaire or DMX decoder, ensure to Press Zone 1, 2, or 3 on the controller to control desired zone.

Example of DMX Addressing Display




PINOUT CONNECTION GUIDE

The following diagrams/tables indicate the appropriate connections for patching your own CAT5/RJ45, and XLR-3 splice cables. These diagrams are for general reference and may slightly differ between different cable manufacturers.



Pin No.	Wire Color	Function
1	White/Orange	Data +
2	Orange	Data -
3	White/Green	None
4	Blue	None
5	White/Blue	None
6	Green	None
7	White/Brown	May be used as 2nd ground
8	Brown	Ground

Pin No.	Function
1	Ground
2	Data -
3	Data +



DYNAMIC MODE CHART




The Dynamic Mode tool plays factory-programmed scenes. Choose up to 10 different scenes. Short press switches/pauses the mode. Long press adjusts speed of the dynamic mode.

Mode	Description
1	Fade 1 - B M R O Y G C
2	Fade 2 - B G O W C M B
3	Fade 3 - R W C G C W B W
4	Skip 1 - R Y W C G W B M W Y
5	RGB Fade In/Out
6	RGB Fade In
7	RGB Fade Out
8	RGB Skip
9	Fade 4 - B M O G C
10	Fade 5 - W Y W M C W G W M C
11	All Channels Off

SYSTEM DIAGRAM

The following diagram is provided as an example system design. CAT5 (RJ45 connections) data cables are the most cost-effective solution for transmitting DMX-512 signals. XLR-3 cables may also be installed but require an additional adapter for connecting to DMX decoders. Always review each component installation guide for detailed and up-to-date wiring instructions. Install in accordance with NEC and local regulations.



* Driver may not require a fault ground connection. Refer to driver specifications for additional information.

** Install a compatible Class 2 constant voltage driver. It is recommended to load the driver no more than 80% its labeled rating for maximum longevity.

† Refer to driver specifications for a compatible junction box.

†† See luminaire specifications for maximum series run limits.

TROUBLESHOOTING

For thorough troubleshooting of LED strip light and luminaires, see LED luminaire installation guides.

LED luminaires not responding to touch

1. Ensure the blue indicator light is on by pressing 'Power.' A red indicator signifies the device is off. The blue indicator light will blink rapidly when pressing/holding any key on the touch pad.
2. Ensure the appropriate zone number was pressed prior to controlling the DMX decoder/luminaire. For example, if you know the luminaire is addressed to zone 1, press '1' prior to controlling.
3. Ensure the individual zone has not been turned off. Long pressing zones 1-3 will turn the specific zone ON/OFF. Additionally, long pressing R, G, B, W will increase/decrease individual brightness and short pressing will turn R, G, B, W ON/OFF.
4. Ensure the DMX decoder/luminaire is addressed properly. For example, address '001' will respond to zone 1 of the controller. See 'Setting the DMX Address' for additional addressing information.

LED luminaire responding incorrectly

Ensure all wiring connections are correct. Reversing the Data + and Data - will cause lights to flicker and not respond to controller.

1. Check power connections of all components (drivers, DMX decoders/luminaires, DMX controller).
2. Check DMX Data connections - See **Pinout Connection Guide** and **System Diagram** for RJ45 hard-wiring connections.
3. Check DMX decoder connections – See **System Diagram** for CH 1-4 connections.

ADDITIONAL RESOURCES

Visit the online product page at www.DiodeLED.com for additional product specifications & warranty information.

- **DMX WALL MOUNT ZONE CONTROLLER SPECIFICATION SHEET**

For full specifications.

- **VOLTAGE DROP CHARTS**

Use to specify appropriate wire gauge for installation. Available at the 'Resources' page at www.DiodeLED.com.



Toll Free: 877.817.6028 | Fax: 415.592.1596 | www.DiodeLED.com | info@DiodeLED.com
© 2015 Elemental LED Inc. All rights reserved. Specifications are subject to change without notice.