

Features

- 1.5 pole (1 pole with shunt) 30 & 40 amp to 2 pole 20, 25, 30 & 40 amp.
- Features lug, spade terminals and protective covers
- Compact size
- Universal galvanized mounting plates
- ARI 780/790 standards
- Brass/copper terminals
- Quick connect and screw terminals on coil.
- Snap on auxiliary contacts available
- cURus approved



1 Pole with Shunt and 2 Pole Models

Part #	Poles	Full Load Amps.	Coil Voltage 50/60	Locked Rotor Amps			Resistive Amps.	Termination	Furnas #
				240V	480V	600V			
DP-1P30A24	1.5	30	24	180	150	120	40	Screw Type	45EG10AJA
DP-1P30A120	1.5	30	120	180	150	120	40		45EG10AFA
DP-1P30A240	1.5	30	208/240	180	150	120	40		45EG10AGA
DP-1P40A24	1.5	40	24	240	200	160	50	Box Lug	45GG10AJAL, 45FG10AJA, 45GG10AJA
DP-1P40A120	1.5	40	120	240	200	160	50		45GG10AFAL, 45FG10AFA, 45GG10AFA
DP-1P40A240	1.5	40	208/240	240	200	160	50		45GG10AGAL, 45FG10AGA, 45GG10AGA
DP-2P20A24	2	20	24	120	100	80	30	Box Lug	45CG20AJ
DP-2P20A120	2	20	120	120	100	80	30		45CG20AF
DP-2P20A240	2	20	208/240	120	100	80	30		45CG20AG
DP-2P25A24	2	25	24	150	125	100	35	Box Lug	45DG20AJ
DP-2P25A120	2	25	120	150	125	100	35		45DG20AF
DP-2P25A240	2	25	208/240	150	125	100	35		45DG20AG
DP-2P30A24	2	30	24	180	150	120	40	Screw Type	45EG20AJ
DP-2P30A120	2	30	120	180	150	120	40		45EG20AF
DP-2P30A240	2	30	208/240	180	150	120	40		45EG20AG
DP-2P40A24	2	40	24	240	200	160	50	Box Lug	45GG20AJL
DP-2P40A120	2	40	120	240	200	160	50		45GG20AFL
DP-2P40A240	2	40	208/240	240	200	160	50		45GG20AGL