

Project:

Type:

Prepared By:

Date:



UPC: 192552000338

Features and Benefits

- Illuminates entire LED load at reduced output under emergency mode
- One Piece Design with Metal Housing
- 2-in-1 LED test switch and indicator light included
- Evaluated to UL 924 requirements
- Not for use with dimmers
- 90 Minute operation in Emergency Mode
- UL Listed
- Operating Temperature: 32°F/0°C to 122°F/50°C

Technical Specifications

Performance

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Construction

Bulb Shape:
Cuboid

Enclosure Material:
Metal

Electrical

Input Voltage:
120-277V AC

Operating Frequency:
50/60Hz

Operating Temperature:
0°C to 50°C

Other

Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Listings:
UL Listed

Environment:
Damp

T20 Compliant:
Yes

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15B of the FCC Rules

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
14	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	1	0	0	0
PALLET	1500	0	0	0

Dimension

