

Project:

Type:

Prepared By:

Date:



UPC: 019813834467



### Features and Benefits

Illuminates entire LED load at reduced output under emergency mode  
 One Piece Design with Metal Housing  
 2-in-1 LED test switch and indicator light included  
 Evaluated to UL 924 requirements  
 Not for use with dimmers  
 90 Minute operation in Emergency Mode  
 UL Listed  
 Operating Temperature: 32°F/0°C to 122°F/50°C

## Technical Specifications

### Performance

#### Product Type:

Driver

#### Input Wattage:

5W

### Construction

#### Material:

Metal Casing

### Electrical

#### Power Factor:

&gt;0.4 @ 120V

#### Input Voltage:

120-277V AC

#### Operating Frequency:

50/60 Hz

### Electrical Characteristics

#### Input Current @ 120V:

100mA

#### Rated Output Current:

Load Dependent

#### Max Output Voltage:

300Vdc

### Installation

#### Installation Type:

Emergency Back up for Double Ended or Single +  
 Double ended tubes

### Compliance

#### UL Listed:

Yes

#### NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

#### CEC Status:

Lawful for sale in California

### Other

#### Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	13.6	10.6	8.1
PALLET	1500	45.3	39.4	49.2

Dimension

