

TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.






FEATURES

- Title 24 Compliant*
- Energy Star® rated
- High performance exterior rated LED pendant
- Includes three extension rods and a flat canopy
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 20% (120V only)
 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<div><p>DS-PD05 5" 27W</p></div>		S927 2700K	90*	1680	8526	62	 <p>18°</p>	<div>BK Black</div> <div>WT White</div> <div>BZ Bronze</div> <div>GH Graphite</div> <div></div>
		S27 2700K	85	1800	9151	67		
		S930 3000K	90*	1700	8639	63		
		S30 3000K	85	1995	10126	74		
		S35 3500K	85	2190	11118	81		
		S40 4000K	85	2260	11483	84		
		N927 2700K	90*	1730	5513	64	 <p>25°</p>	
		N27 2700K	85	1855	5918	69		
		N930 3000K	90*	1750	5587	65		
		N30 3000K	85	2055	6548	76		
		N35 3500K	85	2255	7190	84		
		N40 4000K	85	2330	7426	86		
		F927 2700K	90*	1725	4246	64	 <p>33°</p>	
		F27 2700K	85	1850	4557	69		
		F930 3000K	90*	1745	4302	65		
		F30 3000K	85	2045	5043	73		
		F35 3500K	85	2245	5537	83		
		F40 4000K	85	2320	5719	86		

DS-PD05-_____-_____-

Example: DS-PD05-S930-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

				Finish
	Swivel Canopy Suspension Kit	DS-PDSK	Seismic swivel tilts up to 45° to accommodate sloped ceiling Includes swivel canopy and two 24" extension rods Extendable up to 96" using DS-PDX24 Can be field cut Damp location listed	BK Black WT White BZ Bronze GH Graphite
	Extension Rod	DS-PDX24	One 24" extension rod for DS-PDSK Can be field cut	BK Black WT White BZ Bronze GH Graphite

Example: **DS-PDSK-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-PD06

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



Included extension rods

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting.

Comes in various light distribution and beam angle options.

FEATURES

- Energy Star® rated
- High performance exterior rated LED pendant
- Includes three extension rods and a flat canopy
- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 20% (120V only)
0-10V: 100% - 20% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<div><p>DS-PD06 6" 36W</p></div>	S927	2700K	90	1875	8911	51	<p>19°</p>	<div><div>BK Black</div><div>WT White</div><div>BZ Bronze</div><div>GH Graphite</div></div> <div></div>
	S27	2700K	85	2400	11392	65		
	S930	3000K	90	2000	9500	54		
	S30	3000K	85	2170	10317	59		
	S35	3500K	85	2500	11884	68		
	S40	4000K	85	2450	11639	66		
	N927	2700K	90	1830	4642	49	<p>30°</p>	
	N27	2700K	85	2340	5935	63		
	N930	3000K	90	1950	4949	53		
	N30	3000K	85	2120	5374	57		
	N35	3500K	85	2440	6191	66		
	N40	4000K	85	2390	6063	65		
	F927	2700K	90	1840	3310	50	<p>40°</p>	
	F27	2700K	85	2355	4231	64		
	F930	3000K	90	1965	3528	53		
	F30	3000K	85	2130	3832	58		
	F35	3500K	85	2455	4414	66		
	F40	4000K	85	2405	4323	65		

DS-PD06-_____ - _____

Example: **DS-PD06-S930-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD06

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

				Finish
	Swivel Canopy Suspension Kit	DS-PDSK	Seismic swivel tilts up to 45° to accommodate sloped ceiling Includes swivel canopy and two 24" extension rods Extendable up to 96" using DS-PDX24 Can be field cut Damp location listed	BK Black WT White BZ Bronze GH Graphite
	Extension Rod	DS-PDX24	One 24" extension rod for DS-PDSK Can be field cut	BK Black WT White BZ Bronze GH Graphite

Example: **DS-PDSK-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-PD08

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



Included extension rods

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.





FEATURES

- Energy Star® rated
- High performance exterior rated LED pendant
- Includes three extension rods and a flat canopy
- Solid aluminum construction
- 43° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 80,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<div></div> <div>DS-PD08 8" 54W</div>	S927	2700K	90	2860	20455	53	<div>14°</div> 	<div><div>BK</div>Black</div> <div><div>WT</div>White</div> <div><div>BZ</div>Bronze</div> <div><div>GH</div>Graphite</div>
	S27	2700K	85	3365	24065	62		
	S930	3000K	90	3230	21796	60		
	S30	3000K	85	3670	24490	68		
	S35	3500K	85	4015	28660	74		
	S40	4000K	85	3650	15121	68		
	N927	2700K	90	2890	6851	54	<div>28°</div> 	
	N27	2700K	85	3400	8060	63		
	N930	3000K	90	3318	7907	61		
	N30	3000K	85	3770	8885	70		
	N35	3500K	85	4005	9390	74		
	N40	4000K	85	3675	12052	68		
	F927	2700K	90	2886	4633	53	<div>40°</div> 	
	F27	2700K	85	3395	5450	63		
	F930	3000K	90	3322	5407	62		
	F30	3000K	85	3775	6075	70		
	F35	3500K	85	4005	6490	74		
	F40	4000K	85	3725	5443	69		

DS-PD08-_____-_____-

Example: DS-PD08-S930-WT

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD08

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

				Finish
	Swivel Canopy Suspension Kit	DS-PDSK	Seismic swivel tilts up to 45° to accommodate sloped ceiling Includes swivel canopy and two 24" extension rods Extendable up to 96" using DS-PDX24 Can be field cut Damp location listed	BK Black WT White BZ Bronze GH Graphite
	Extension Rod	DS-PDX24	One 24" extension rod for DS-PDSK Can be field cut	BK Black WT White BZ Bronze GH Graphite

Example: **DS-PDSK-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760