



Project:	Type:
Prepared By:	Date:

Driver Info Type Constant Current 120V 114mA 208V N/A 240V N/A 277V N/A Input Watts 12W	LED Info Watts 12W Color Temp 4000K Color Accuracy 90 CRI L70 Lifespan 50,000 Hours Lumens 863 Efficacy 62.5
---	--

Technical Specifications		
Performance		Construction
Product Type: Disk Surface Mount / Retrofit	R9 Value: High color performance with R9 greater than or equal to 50	Size: 4"
Input Wattage: 12W	Dimmable: TRIAC and ELV dimming compatibility	Shape: Round
Lumens (Nominal): 750lm	LEDs: Backlit LED Technology	Housing Material: Stamped aluminum construction
Efficacy: 62.5 lm/W	Lifespan: 50,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations	Finish: White
Color Accuracy (CRI): 90 CRI	LED Characteristics	
	Color Temperature: 4000K	

Technical Specifications (continued)

Construction**Trim Style:**

Smooth

Lens:

Toolless, twist-and-lock frosted polycarbonate diffusion lens

Beam Angle:

110°

Electrical**THD:**

50%

Power Factor:

≥0.9

Input Voltage:

120V

Operating Frequency:

60Hz

Operating Temperature:

-30°C - 40°C

Note:

All values are typical (tolerance +/- 10%)

Installation**Mounting:**

Install from below design.

Suitable for installation in many.

3-1/2" and 4" octagon and round electrical junction boxes.

Compatible with compact/pancake junction boxes.

Bracket Adapter, Screws, and wire nuts included.

Other**Equivalency:**

65W

Technology EQ:

Incandescent

Base Type:

E26 socket available as separate retrofit accessory

Warranty (Years):

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Compliance**Safety Listing:**

UL Listed, UL Classified

Environment:

Damp

Fixture Rating:

Open

IC Rated:

Suitable for direct contact with insulation

ENERGY STAR:

This product is ENERGY STAR® Version 2.2 Certified.

T24 JA8 Compliant:

Can be used to conform with the requirements of California Title 24 Part 6.

RoHS:

Mercury and UV free. RoHS-compliant components.


FCC:

Complies with Part 15 of the FCC Rules

Model Number:

DLS0052(DSK34-4R12940120WS)

Dimensions



Features

- Super low profile backlit LED with driverless design
- Stamped aluminum housing
- New construction or retrofit applications
- Simple and quick installation from below the ceiling
- Installs on standard 4" and 6" junction boxes
- Can be retrofitted to existing downlight housings with option accessory
- Suitable for Damp locations
- Dimmable down to 5% on compatible dimmers
- 5-Year, Limited Warranty

Ordering Matrix

Family		Size	Shape	Wattage	CRI/Color Temp	Voltage	Finish	Trim
DSK34	-	4	R	12	940	120	W	S
		4 = 4"	R = Round	12 = 12W	950 = 90 CRI, 5000K	120 = 120V	W = White	S = Smooth
		6 = 6"		16 = 16W	940 = 90 CRI, 4000K			
					935 = 90 CRI, 3500K			
					930 = 90 CRI, 3000K			
					927 = 90 CRI, 2700K			