

Pex™ 3" Square Adjustable Pinhole

Pex™ precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation



Features



- 3" Square Adjustable Pinhole.]
- 358° Rotation.
- 30° tilt (for EL386ICA), 15° tilt (for EL390 Series).
- Convenient twist-lock design for easy installation.
- Lamp: Koto™ LED Module.
- 4 3/8" Sq.

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module.

Lamp: Koto™ LED Module only.



Dimensions:

Options



Black Reflector
with White Ring



All Black



All Bronze



Black Reflector
with Nickel Ring



All White

Product Number

Item	Finish
ELK3327BB	All Black

Product Number Builder Example: ELK3327W

Pex™ 3" Square Adjustable Pinhole

ELK3327

Finish

W

All White

B

Black Refl. / White Ring

BB

All Black

BZ

All Bronze

N

Black Refl. / Nickel Ring

Compatible Products

For use with Koto™ System 3" Trims



Koto™ Commercial Construction LED Light Engine



ELK19 ELK21
Koto™ LED Light Engine

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 850 lm	27D 2700K	(blank) 38° lens (Standard)
	21 1100 lm	30D 3000K	-S 18° lens
		35D 3500K	-N 25° lens
		40D 4000K	-W 60° lens
		SDD Sunset Dimming	

ACCESSORIES



Lens
EP731C 18° Lens
EP732C 25° Lens
EP734C 60° Lens



Reflectors
EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Hex Louver
L45
For a better glare shield



Linear Louver
L46
For a wide rectangular illumination pattern



Spread Louver
L47
For a symmetrical broadening of light beams



Clear Lens
L48
Protective clear glass lens

3" Commercial Construction Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated
3" ICA Housing - 7 1/2" Height
New Construction



3" ICA Shallow Maximum
Adjustability Housing - 4" Height
New Construction



3" ICA Housing - 5 1/2" Height
New Construction

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
ELK39FICA	120V - Triac/ELV	E3LK76ICA	120V - Triac/ELV	E3LK65ICA	120V - Triac/ELV
ELK39FICAD	120/277V - 0-10V/Triac/ELV	E3LK77ICAD	120/277V - 0-10V/Triac/ELV	E3LK65ICA-EM1	120V - Triac/ELV Emergency Battery Back-up (90 min)
				E3LK66ICAD	120/277V - 0-10V/ Triac/ELV
				E3LK66ICAD-EM1	120/277V - 0-10V/ Triac/ELV Emergency Battery Back-up (90 minute)



3" ICA Housing - 5 1/2" Height
Remodel

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV