EXIT34-RG/E





Project:	Туре:
Prepared By:	Date:

# **Technical Specifications**

#### **Performance**

### **Product Type:**

Exit Sign

#### Description:

Ultra-economy exit sign with universal faces, options for red or green letters, and 90 minutes of emergency backup.

# Input Wattage:

1W @120V and 277V

### **Electrical**

# **Power Factor:**

≥0.9 @ 120V; ≥0.4 @ 277V

# Input Voltage:

Dual 120/277 Voltage

#### Operating Frequency (Hz):

60Hz

### Input Current @ 120V (mA):

90mA

# Input Current @ 277V (mA):

90mA

### **Dual Voltage Circuit Operation:**

No

# **Operating Temperature:**

32°F to 122°F (0°C to 50°C)

### **Emergency Illumination:**

90 minutes

#### **Battery Backup:**

Yes

#### **Battery Type:**

Nickel Cadmium

# **Battery Voltage:**

1.2V

# Recharge Time Required:

24-hours

# **Battery Operating Temperature:**

32°C to 122°C (0°F to 50°F)

# **Storage Temperature:**

68°F to 86°F (20°C to 30°C)

### Storage Shelf Life:

3 years before the initial charge. 5 years after initial charge.

# Self Diagnostics:

No, manual test only

### **Remote Test Switch:**

No

### Installation

#### **Mounting Method:**

Back/Top/End

# **Mounting Type:**

Wall/Ceiling Mount

# **Cold Weather Rated:**

No

#### Construction

#### Shape:

Rectangle

### **Housing Material:**

Thermoplastic

# **Panel Material:**

Thermoplastic

# Panel Color:

White

#### **Letter Color:**

Red/Green

# **Housing Color:**

White

EXIT34-RG/E



# **Technical Specifications (continued)**

#### **Number of Faces:**

Universal Single/Double Face

#### **Arrow Direction:**

No Arrow

#### Sign Format:

Stencil

# **Remote Capacity:**

Nο

#### Compliance

# Listings:

UL924 Listed, NFPA 101 (current Life Safety Code), NEC and OSHA illumination standards

#### **Environment:**

Suitable for indoor use in dry and damp environments

# IP Rating:

Indoor

# **Certification Model Number:**

EZRXTEU2RGWEM

# T20 Compliant:

Can be used to conform with the requirements of California Title 20

# California Title 24 JA8 Compliant:

Not applicable

# California Energy Commission (CEC) Status:

Lawful for Sales in California

# FCC:

Complies with Part 15 of the FCC Rules

# Other

# 5 Yr Limited Warranty:


The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Battery is prorated.

# **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.





# **Features**

- Universal faces with color letters
- Durable thermoplastic design
- Complies with California Title 20 requirements

Ordering Matrix				
Family	Face	Exit Sign Letter Color	Battery Backup	Housing
EXIT34		RG	/E	
	<b>Blank</b> = Universal Faces	Blank = Red G = Green RG = Red/Green Selectable	Blank = No Battery Backup /E = Battery Backup	Blank = White Housing B = Black Housing