



Color: White

Weight: 13.2 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

Type	Constant Current
120V	0.21A
208V	0.12A
240V	0.10A
277V	0.09A
Input Watts	24.3W

LED Info

Watts	25W
Color Temp	4000K (Neutral)
Color Accuracy	81 CRI
L70 Lifespan	60,000
Lumens	2,878
Efficacy	118.4 LPW

Technical Specifications**Listings****UL Listing:**

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

DLC Product Code: PMM37GPO

LED Characteristics**Note:**

All values are typical (tolerance +/- 10%)

Lifespan:

60,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

LEDs:

Long-life, High efficiency, micro-power, surface mount LEDs

Construction**Maximum Ambient Temperature:**

Suitable for use in -30°C (-22°F) to 50°C(122°F)

IC Rating:

Suitable for insulated ceilings

Lens:

Frosted polystyrene

Mounting:

Recessed ceiling

Housing:

Lightweight aluminum housing, steel pan and junction box

Installation:

Standard integral T-bar clips secure the fixture to T-bars and prevent T-system separation

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Electrical**Dimming Driver:**

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims as low as 10%.

Driver:

Constant Current, Class 2, 120-277V, 50/60Hz, 120V: 0.21A, 208V: 0.12A, 240V: 0.10A, 277V: 0.09A

THD:

11.1% at 120V, 7.2% at 277V

Power Factor:

100% at 120V, 95.3% at 277V


Other**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at www.rablighting.com/legal#warranty

Technical Specifications (continued)**Other****Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- Perfect for shallow plenums
- Even and diffuse ambient illumination, ideal for spaces where glare-free lighting is required
- 0-10V dimmable driver, standard

Ordering Matrix

Family	Size	Wattage	CCT/CRI	Driver	Suffix
EZPAN	2X2	25	N	/D10	SRZ
	2X4 = 2' x 4'	25 = 25W	N = 4000K (Neutral)	/D10 = 0-10V Dimming	SRZ = Contractor Grade
	2X2 = 2' x 2'	35 = 35W			