

SPECIFICATION & FEATURES

DESCRIPTION:

Orbit Industries' bottom mount with stud hammer on flange clips can be independently mounted to any surface. Tap on flanges from 1/8" to 3/4" with the hammer. Captive threaded stud helps minimize other hardware. Further attachment is possible with rods or straps.

HAMMER ON FLANGE CLIPS BOTTOM MOUNT WITH STUD 1/8" ~ 3/4" FLANGE



CERTIFICATION:

UL file E328572, conforms to UL 2239.



FEATURES:

- Spring Steel
- Can be used to support boxes, fixtures or other attachments from beam flanges
- Only hammer needed for installation

CONFIGURATION DATA:

Part No.	Flange Thickness	Rod Size	Thread Size	Screw Length	Load Capacity			Std. Pkg.
					Vertical Rod	Horizontal Rod	Vertical Strap	
FM24S	1/8" ~ 1/4"	1/4"	1/4" - 20	3/8"	100 LB	25 LB	75 LB	100
FM58S	5/16" ~ 1/2"	1/4"	1/4" - 20	3/8"	100 LB	25 LB	75 LB	100
FM912S	9/16" ~ 3/4"	1/4"	1/4" - 20	3/8"	100 LB	25 LB	75 LB	100

