

GY6.35 Base

Products > Halogen > Low Voltage JC Bi-Pin > GY6.35 Base

- 6, 12 & 24 Volt
- Provides UV protection
- Ideal for commercial applications; most commonly used in task lighting and displays



Chandelier Landscape Recessed Track

Technical Specifications

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner Pk. / Master Ctn.	Description	Color Temperature	Lumens	Average Hours	MOL
35	T3	GY6 35	651035	Q35GY6/6	6	10 / 50	Clear	-	670	2000	1 5/8"
35	T3	GY6.35	650035	Q35GY6/12	12	10 / 50	Clear	2800K	650	2000	1 5/8"
35	T3	GY6.35	650036	Q35GY6F/12	12	10 / 50	Frost	2800K	640	2000	1 5/8"
35	T3	GY6.35	651036	Q35GY6/24	24	10 / 50	Clear	2800K	650	2000	1 5/8"
50	T3	GY6.35	650050	Q50GY6/12	12	10 / 50	Clear	2800K	900	2000	1 5/8"
50	T3	GY6.35	650051	Q50GY6F/12	12	10 / 50	Frost	2800K	850	2000	1 5/8"
50	T3	GY6.35	651050	Q50GY6/24	24	10 / 50	Clear	2800K	820	2000	1 5/8"

Watts	Bulb Type	Base	Item #	Ordering Code	Volts	Inner Pk. / Master Ctn.	Description	Color Temperature	Lumens	Average Hours	MOL
75	T3	GY6.35	650075	Q75GY6/12	12	10 / 50	Clear	2800K	1400	2000	1 5/8"
75	T3	GY6.35	651075	Q75GY6/24	24	10 / 50	Clear	2800K	1350	2000	1 5/8"
100	T3	GY6.35	650100	Q100GY6/12	12	10 / 50	Clear	2800K	2200	2000	1 5/8"
100	T3	GY6.35	651100	Q100GY6/24	24	10 / 50	Clear	2800K	1800	2000	1 5/8"