

- PRODUCT DATA SHEET H14R.2





H14R.2

PRODUCT DESCRIPTION

Suggestions from users and experts have been incorporated into the development of the Ledlenser H14R.2. In this way, the innovative rotation switch concept for operation is more convenient than ever before, the recharging via USB cable more flexible and the operating time can be extended as required thanks to the additional battery packs. The entire lighting and the enormous luminous flux of up to 1000 lumen¹ are some of the best that Ledlenser headlamps have to offer.

- Ready for the extreme runs with exchangeable or normal battery
- From the homogeneous circle of close range lighting (focused) to a sharply bundled long-distance beam (defocused) – the patented³ Advanced Focus System with reflector lense enables efficient, tailored lighting
- Individual headlamp adaptation to the current usage situation Smart Light Technology
- Quick modification of the light cone with just one hand Rapid Focus
- More security and visibility rear light with two functions and battery indicator



| TECHNICAL DATA | |
|------------------------------|------------------------|
| Head diameter [mm] | 37 |
| Weight incl. batteries [g] | 340 |
| Weight without batteries [g] | 250 |
| Focus function | Yes |
| Head material | Aluminum alloy |
| Tube material | PC |
| Optic | Plastic lense (PMMA) |
| Headband material | Elastic fabric |
| Headband type | Side overhead headband |
| Head movement type | Stepped movement |
| Head movement angle [°] | 90 |
| Headband specifications | Detachable, |
| | Elastic, |
| | Washable |

| POWER SUPPLY | |
|--|---------------------------|
| Power source type | Rechargeable battery |
| Battery quantity | 1 |
| Battery type | Li-ion |
| Battery description | 2x18650 Battery Pack 3.7V |
| Total battery voltage [V] | 3.7 |
| Total battery capacity [mAh] | 4400 |
| Total battery energy ² [Wh] | 16.28 |
| Rechargeable | Yes |
| UN number | UN 3481 |
| Charging time ⁵ [min] | 480 |
| Energy modes | Constant Current, |
| | Energy Saving |
| Energy status indicator | Battery Indicator, |
| | Charge Indicator, |
| | Low Battery Warning |
| Usable batteries | AA Alkaline 1.5V, |
| | AA NIMH 1.2V, |
| | CR 123A 3V |

| FURTHER SPECIFICATI | ONS |
|--------------------------------|------------|
| IP class | IPX4 |
| Drop test (drop height) [m] | 2 |
| Working temperature range [°C] | -20 to +40 |

LIGHT FUNCTIONS

Low Power, Power, Boost, Blink

| LIGHT SOURCE | |
|-----------------------------|--------------|
| Amount LEDs | 1 |
| LED type | Xtreme LED |
| Color | White |
| Color temperature [K] | 6000 to 8000 |
| Color rendering index (CRI) | 65 |

| LIGHT VALUES | 5 | | |
|--------------------------------|-------|-------|---------------------|
| ANSI – Energy Saving | Boost | Power | Mid Power Low Power |
| Light output ¹ [lm] | 1000 | 450 | 60 |
| Beam distance ¹ [m] | 300 | 200 | 70 |
| Run time ¹ [h] | 6 | 12 | 35 |

SWITCH

Front Switch, Multifunctional Switch

FEATURES

Rear light , Dimmable , Transportation lock

TECHNOLOGIES

Advanced Focus System³, Rapid Focus, Smart Light Technology, Temperature Control System, Dual Power Source



H14R.2

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

| Type of packaging | Box |
|-----------------------|---|
| Scope of delivery | 1 set of rechargeable batteries, Extension cable, USB cable, USB power adapter |
| Item No. | 7299-R |
| Customs tariff number | 85131000 |
| Color | black |
| MSRP price (€) | 169.90 |

| SINGLE PACKAGE | |
|---------------------------|------------------|
| Dimensions W x H x D [cm] | 13.7 x 10 x 11.5 |
| Gross weight [g] | 548 |
| GTIN-13 | 4029113729932 |

| INNER CARTON | |
|---------------------------|--------------------|
| Unit | 6 |
| Dimensions W x D x H [cm] | 31.9 x 28.5 x 12.7 |
| Gross weight [g] | 3450 |
| GTIN-13 | 4029113729949 |

| EXPORT CARTON | |
|---------------------------|--------------------|
| Unit | 12 |
| Dimensions W x D x H [cm] | 34.6 x 31.4 x 28.5 |
| Gross weight [kg] | 7.83 |
| GTIN-13 | 4029113729956 |



—H14R.2

ACCESORIES

| PRODUCT CATEGORY | ITEM NUMBER | PRODUCT NAME | MSRP |
|----------------------------|-------------|---|---------|
| Fastenings / Brackets | 0363 | Universal Mounting Bracket Type A | 17.90 € |
| Color filter / Signal caps | 0313-F | Color Filter Set + 1x Rollprotection 37mm | 19.90 € |
| Charger / Cable | 0380 | USB Car Charger | 9.90 € |
| Charger / Cable | 0389 | USB Power Supply and Adapter Cable | 14.90 € |
| Charger / Cable | 0396 | Extension Cable Type A | 8.90 € |
| Battery | 7795 | Li-Ion rechargeable Battery Pack 4400 mAh | 39.90 € |
| Fastenings / Brackets | 0393 | Helmet Connecting Kit Type A | 14.90€ |
| Color filter / Signal caps | 100879 | Color Filter Set 37mm | 19.90€ |
| Fastenings / Brackets | 0359 | Helmet Band Fixing Clip (4x) | 6.90 € |
| Charger / Cable | 0413 | USB Adapter Cable | 9.90 € |
| Battery | 500831 | XEO PowerBox including Bag | 150.00€ |
| Roll Protections | 0313 | Roll Protection 37mm | 9.90 € |
| Battery | 500980 | 4x AA Alkaline Ionic | 3.49 € |



H14R.2

PRODUCT SERIES

The Headlamps of the Ledlenser H-Series Let somebody else do the headwork.

The "H" in H-Series stands for "head". Because with the headlamps of the H-Series everything revolves around the most important part of the body - the head. The intuitive handling, ergonomic design and the brightest LED light of this first-class headlamp ensure that you'll see more than just the light. And you can also fully rely on us for servicing.

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurements according to ANSI FL1 on the respective setting. Average values, in some cases, deviations by +/- 15 % may occur due to technical reasons. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If no setting is explicitly indicated, measurement is based on "energy saving mode."

- 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.
- 3) EP Patent 1880139, US Patent 7,461,960
- 4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the products of the "Solidline" series, Ledlenser K1 and Ledlenser K2. The warranty does not apply to defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 7, 42699 Solingen, Germany. More information: ledlenser.com/warranty
- 5) Charging time varies by hardware used.

