



LOW VOLTAGE

- 350° horizontal rotation and 90° vertical aiming
- Available in H, L, J and J2 track systems
- Abrasion resistant powder coated finish



- Recessed lamp position for minimal glare
- May be fitted with factory installed extensions




System			Finish		Lamp	Dimensions		
L	H	J/J2	BK	WT	MR16	L	W	H
LHT-808	HHT-808	JHT-808	•	•	50w max	3 3/8"	2 3/4"	6 1/4"
LHT-808L	HHT-808L	JHT-808L	•	•	75w max	3 3/8"	2 3/4"	6 1/4"

Order lamp separately. Clear lens included. See pages 193-194 for lens options.

Model shown **HHT-808-WT**



- Available adjustable barn door to control glare from lamp
- May be fitted with factory installed extensions



System			Finish		Lamp	Dimensions		
L	H	J/J2	BK	WT	MR16	L	W	H
LHT-801	HHT-801	JHT-801	•	•	50w max	3"	2 1/2"	6"
LHT-801L	HHT-801L	JHT-801L	•	•	75w max	3"	2 1/2"	6"

Order lamp separately. Clear lens included. See pages 193-194 for lens options.

Model shown **HHT-801-WT**



Barn door accessory (order separately)		BK	WT
801BD		•	•

Finish Key BK-Black, WT-White

