

FLEXRAIL1™ components



120V MONORAIL SECTION

| | |
|---|--------|
| HM1-T4 | 4feet |
| HM1-T8 | 8feet |
| Finish | DB, PT |
| Bendable 120v monorail 2400w down rated to 1920w maximum. Includes two matching end caps. | |



FLEXRAIL1™ BENDING MACHINE

| | |
|--|--|
| HM1-BM | |
| Used to make smooth, consistent bends. For small radius bends. Clamps onto work benches or flat surfaces up to 2" max. | |



STEM POWER FEED CONNECTOR

| | |
|------------------|--------|
| HM1-PCT6 | 6" |
| HM1-PCT12 | 12" |
| HM1-PCT24 | 24" |
| HM1-PCT36 | 36" |
| HM1-PCT48 | 48" |
| Finish | DB, PT |

Both a support and power feed. May be placed anywhere along the length of 120v monorail



FLEXIBLE CEILING POWER FEED

| | |
|------------------|-----|
| HM1-PCC12 | 12" |
| HM1-PCC24 | 24" |
| HM1-PCC36 | 36" |
| HM1-PCC48 | 48" |
| HM1-PCC96 | 96" |

Finish DB, PT

Used for powering sloped ceilings or custom suspension lengths



STANDARD CEILING STANDOFF

| | |
|----------------|-----|
| HM1-X6 | 6" |
| HM1-X12 | 12" |
| HM1-X24 | 24" |
| HM1-X36 | 36" |
| HM1-X48 | 48" |

Finish DB, PT

Supports 120v monorail for flat ceilings and surfaces



SLOPED CEILING STANDOFF

| | |
|-----------------|---------|
| HM1-XS6 | 7 3/4" |
| HM1-XS12 | 13 3/4" |
| HM1-XS24 | 25 3/4" |
| HM1-XS36 | 37 3/4" |
| HM1-XS48 | 49 3/4" |

Finish DB, PT

Supports 120v monorail for sloped ceiling Accommodates angles up to 45°



T-BAR CEILING STANDOFF

| | |
|-----------------|-----|
| HM1-TB6 | 6" |
| HM1-TB12 | 12" |
| HM1-TB24 | 24" |
| HM1-TB36 | 36" |
| HM1-TB48 | 48" |

Finish DB, PT

Conceals a T-Bar clip under the canopy for standard 1" T-Bar ceilings



FIELD SHORTENING ADAPTER

| | |
|----------------|--------|
| HM-XADJ | |
| Finish | DB, PT |

Used for standoffs or "I" connector rods



ROD COUPLER

| | |
|-----------|--------|
| XI | |
| Finish | DB, PT |

Connects two standoffs or "I" connector rods together to form a longer drop



SLOPED CEILING ADAPTER

| | |
|--------------|--------|
| SK145 | |
| Finish | DB, PT |

Used with standoffs and "I" connectors when mounting HM1 on a sloped ceiling



"I" CONNECTOR

| | |
|----------------|-----|
| HM1-I6 | 6" |
| HM1-I12 | 12" |
| HM1-I24 | 24" |
| HM1-I36 | 36" |
| HM1-I48 | 48" |

Finish DB, PT

Connects two sections of 120v monorail with electrical continuity



"I" DEAD-END CONNECTOR

| | |
|-------------------|-----|
| HM1-IDEC6 | 6" |
| HM1-IDEC12 | 12" |
| HM1-IDEC24 | 24" |
| HM1-IDEC36 | 36" |
| HM1-IDEC48 | 48" |

Finish DB, PT

Connects two sections of 120v monorail with no electrical connection



END CAP

| | |
|---------------|--------|
| HM1-EC | |
| Finish | DB, PT |



VARIABLE ANGLE CONNECTOR

| | |
|-----------------|-----|
| HM1-VA6 | 6" |
| HM1-VA12 | 12" |
| HM1-VA24 | 24" |
| HM1-VA36 | 36" |
| HM1-VA48 | 48" |

Finish DB, PT

Connects two sections of 120v monorail with electrical continuity. Connects at any angle up to 270°

Finish Key DB-Dark Bronze, PT-Platinum



WAC LIGHTING . Responsible Lighting.