


HR-2LD-ET109

2" Tesla™ LED High Brightness Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round, High Brightness downlight trim with glass lens

FEATURES

- 2" aperture
- High Brightness Trim
- Energy Star® rated
- CEC Title 24 Compliant (see below for list of models)
- Wet location listed
- 5° visual cutoff angle for glare control
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. Energy Star®. Wet location listed.
See table below for California Title 24 Compliant for qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	2013 Title 24	Finish
HR-2LD-ET109 High Brightness Energy Star® Wet Location Listed	S 16.5°	27 2700K	85	665	2921	Yes	No	BN Brushed Nickel CB Copper Bronze WT White
		W 3000K	85	730	3786	Yes	No	
		9W 3000K	90	672	2689	Yes	No	
		35 3500K	85	730	3284	Yes	No	
		C 4000K	85	695	3494	Yes	No	
	N 30°	27 2700K	85	635	1415	Yes	No	
		W 3000K	85	705	1669	Yes	No	
		9W 3000K	90	466	1596	Yes	Yes	
		35 3500K	85	705	1627	Yes	No	
		C 4000K	85	670	1554	Yes	No	
	F 53°	27 2700K	85	610	788	Yes	No	
		W 3000K	85	695	1089	Yes	No	
		9W 3000K	90	480	880	Yes	Yes	
		35 3500K	85	690	880	Yes	No	
		C 4000K	85	635	796	Yes	No	

HR-2LD-ET109



-



-



Example: **HR-2LD-ET109F-9W-BN**

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

New Construction

HR-2LED-H09D-ICA IC-Rated, Airtight	120V-277V	HR-2LED-H09D-ICAC IC-Rated, Airtight Chicago Plenum	120V-277V
---	-----------	--	-----------

Remodel

HR-2LED-R09D-A Non-IC, Airtight	120V-277V	HR-2LED-R14D Non-IC	120V-277V
---	-----------	-------------------------------	-----------

REPLACEMENT MODULES

Reflectors

Spot	SL-REF-LUX10-S
Narrow Flood	SL-REF-LUX10-N
Flood	SL-REF-LUX10-F

LED

2700K	85 CRI	LXS8-PW27
3000K	85 CRI	LXS8-PW30
3000K	90 CRI	LXS9-PW30
3500K	85 CRI	LXS8-PW35
4000K	85 CRI	LXS8-PW40

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760