

Xenon and Halogen Button Lights

Recessed or surface mounted, Xenon and Halogen Button Lights offer low profile and shallow installation depths. Ideal for use in shelves, cabinets and displays. Constructed of steel, the fixtures require a Class 2 remote transformer.

- 2 inch cutout template included for recessed installations
- Lamp included
- Requires a Class 2 transformer (sold separately)
- · All steel construction
- Supplied with 72 inch wires
- Dual mounting options
- · Low profile and shallow installation depths are ideal for tight spaces









ustainable Choice




Shown as surface mounted. Total height is 1'



Shown as recessed mounted. Total extension is 1/8

Optimal Choice

- Xenon lamps last 10,000 hours
- Cooler burning than Halogen



XENON BUTTON LIGHT

Model	Lamp			Finish					
	20w max	Color	Life	BK	BN	CB	CH	PB	WT
HR-86	BP20	2700K	10,000 hr.	•	•	•	•	•	•
Model shown HR-86-BK									

Lamp included. Requires a Class 2 remote transformer






Shown as surface mounted. Total height is 1"



Shown as recessed mounted. Total extension is 1/8"

- Halogen lamps emit a warmer light
- Emits a whiter light



HALOGEN BUTTON LIGHT

Model	Lamp			Finish					
	20w max	Color	Life	BK	BN	CB	CH	PB	WT
HR-88	JC-20	3000K	2000 hr.	•	•	•	•	•	•
M									

Model shown HR-88-CB

Lamp included. Requires a Class 2 remote transformer



CLASS 2 ENCLOSED ELECTRONIC TRANSFORMERS

	Input	Output	Dimensions
EN-1260-RB2	120v	12v (1 × 60w)	6 %"×1 %"×1 %"
EN-12120-RB2*	120v	$12v (2 \times 60w)$	6" × 3 ¼" × 2 5%"
EN-12180-RB2*	120v	$12v (3 \times 60w)$	6 3/4" × 3 5/8" × 2 5/8"
EN-12300-RB2*	120v	$12v (5 \times 60w)$	8 ¼" × 4 5/8"× 2 5/8"

*Models with LED indicator lights and interal push in terminals Enclosed Class 2 transformers have multiple outputs in 60w increments.



LENS-45-FR Finish FR For use with HR-86 and HR-88.

Finish Key BK-Black, BN-Brushed Nickel, CB-Copper Bronze, CH-Chrome, FR-Frosted, PB-Polished Brass, WT-White

