3" die cast aluminum downlights











180° SHIELDED WALL WASH 25° ADJUSTMENT FROM VERTICAL

Model	Finish	Trim	
HR-D334	BN WT	Brushed Nickel White	
Lamp		Housing	
MR16 50w max		1 2 3 4	
Order Jama consertely Clear long included			

Order lamp separately. Clear lens included Other lens options see p.231


Model Shown HR-D334-BN




Model		Finish			Trim
HR-D329		CB WT			Copper Bronze White
Lamp				Но	using
MR16	35w max		1	2	3 4
Xenon bi-pin	50w max		1	2	3 4
Order lamp sep Other lens option					

Example HR-D329-WT









PIN HOLE

Model	Finish	Baffle	Trim
HR-D325	BK/WT WT/WT	Black White	White White
Lamp	Housing		
MR16 35w max	1 2 3 4		

Order lamp separately. Clear lens included Other lens options see p.231

Model Shown HR-D325-BK/WT


ETCHED GLASS RING

Model	Finish	Glass	Trim
HR-D332	AM WT	Amber White	White White
Lamp	Housing		
MR16 50w max		1 2	3 4


Order lamp separately. Clear lens included Other lens options see p.231

Model Shown HR-D332-AM









25° ADJUSTMENT FROM VERTICAL

Model	Finish	Trim	
HR-D326	BK BN WT	Black Brushed Nickel White	
Lamp	Housing		
MR16 35w max		1 2 3 4	

Order lamp separately. Clear lens included Other lens options see p.231

Model Shown HR-D326-WT

GLASS CYLINDER

Model	Finish	Glass	Trim	
HR-D333	AM/WT WT/WT	Amber White	White White	
Lamp	Housing			
MR16 50w max	1 2 3 4			

Order lamp separately. Clear lens included Other lens options see p.231


Model Shown HR-D333-AM/WT

3

ELECTRONIC NON-IC REMODEL HOUSING

	110111011	011 10 1121110001110			
	HR-301E	50w max			
Integral Electronic Transformer					






- NON-IC downlight, 3" clearance on all sides must be maintained when insulation is present Integral Electronic Transformer features auto-reset, short circuit, and soft start technologies
- J-Box and transformer accessible through ceiling opening
- UL listed for direct chain wiring to other housings



MAGNETIC NON-IC REMODEL HOUSING

50w max Integral Magnetic Transformer





- NON-IC downlight, 3" clearance on all sides must be maintained when insulation is present
- Integral Electronic Transformer features auto-reset, short circuit, and soft start technologies
- J-Box and transformer accessible through ceiling opening
- UL listed for direct chain wiring to other housings

